



GRENADA

Material	steel pipes \varnothing 20 mm / steel profiles D30 x 35 mm
Connection thread	4 x G1/2"
Testing overpressure	1,3 MPa
Max. operating overpressure	1,0 MPa
Max. operating temperature	110 °C
Number of pipes	15, 19, 24, 32, 38



GRENADA 1135 x 600

Type H/L [mm]	Depth B [mm]	Weight [kg]	Water capacity [l]	Temperature exponent [n]	Heating Output [W]			Recommended power input chrome [W]		Connection span [mm]
					75/65/20 °C	70/55/20 °C	55/45/20 °C	paint [W]	chrome [W]	
695/450	30	5,2	2,5	1,270	298	242	156	300	200	415
695/500	30	5,6	2,7	1,270	327	266	171	300	200	465
695/600	30	6,5	3,0	1,270	384	312	201	400	300	565
695/750	30	7,9	3,6	1,226	462	379	247	500	300	715
935/450	30	7,0	3,3	1,269	391	318	204	400	300	415
935/500	30	7,5	3,6	1,269	429	349	224	400	400	465
935/600	30	8,7	4,1	1,269	504	410	264	500	400	565
935/750	30	10,5	4,8	1,269	612	498	320	600	500	715
1135/450	30	8,4	4,0	1,269	467	380	244	500	300	415
1135/500	30	9,0	4,3	1,269	512	417	268	500	400	465
1135/600	30	10,4	4,9	1,269	602	490	315	600	400	565
1135/750	30	12,6	5,7	1,226	742	608	396	700	500	715
1535/450	30	11,2	5,4	1,268	632	514	331	600	400	415
1535/500	30	12,1	5,8	1,268	693	564	363	700	500	465
1535/600	30	13,9	6,5	1,268	815	663	427	800	600	565
1535/750	30	16,9	7,7	1,226	991	812	530	1000	700	715
1775/450	30	13,1	6,3	1,267	739	601	387	700	500	415
1775/500	30	14,2	6,8	1,267	810	659	424	800	600	465
1775/600	30	16,4	7,7	1,267	952	775	498	1000	700	565
1775/750	30	19,9	9,1	1,226	1170	959	625	1200	800	715

Thermal power measuring follows in accordance with EN 442. Chrome surface treatment reduces heating capacity by ~30 %. Accessories (page 64, 65 and 66) is not part of the radiator.

POSSIBILITY OF THE MIDDLE CONNECTION (per order)

direct middle connection standard

direct middle connection with cover

Connection options

	DGRE 0695 0450...	DGRE 0935 0450...	DGRE 1135 0450...	DGRE 1535 0450...	DGRE 1775 0450...
	DGRE 0695 0500...	DGRE 0935 0500...	DGRE 1135 0500...	DGRE 1535 0500...	DGRE 1775 0500...
	DGRE 0695 0600...	DGRE 0935 0600...	DGRE 1135 0600...	DGRE 1535 0600...	DGRE 1775 0600...
	DGRE 0695 0750...	DGRE 0935 0750...	DGRE 1135 0750...	DGRE 1535 0750...	DGRE 1775 0750...

	A [mm]	X [mm]
Plastic brackets (RAL 9006, 9016)	88-98	73-83
Metal brackets (Other colours)	84-94	69-79