

Technical information

Vescom 3000

2017

application

Vescom 3000 is a wallcovering adhesive for renovation projects where new wallcovering material is installed over different types of wallcovering including PVC.

substrate

Permanent sealed (not breathing) surfaces.

specific properties

Adhesive type	: Resin- and starch-based dispersion adhesive
Brookfield viscosity:	: 37,500 mPa.s (HAT; spindle 6; 20 rpm; 20°C)
Dry solids content	: 62.0%
pH	: 7.5
Colour	: White
Open time	: 15 – 45 minutes
Bonding time	: 1 – 4 hours
Spreading rate	: 150 – 400 g/m ²

VOS EU limit value: The limit values of this product is < 1 g/l VOS in accordance with Directive 2004/42/EC.

The open and bonding time and spreading rate will depend on the substrate, the wallcovering type and the temperature and relative humidity of the materials and the environment.

application

Vescom 3000 is ready for use, (do not dilute).

The adhesive can be applied on the substrate by using a (lamb's wool) roller or paintbrush.

The substrate must be clean, dry, firm and smooth.

cleaning

Non-dried-on adhesive can be easily cleaned using water.

packaging

10 ltr bucket

storage and shelf life

The adhesive must be stored in a unopened pack preferably at room temperature.

The product can be used as normal after defrosting and stirring correctly after freezing (up to -10 °C).

The shelf life of the product is 9 months.