

P2 LEVEL 3 SURGICAL DISPOSABLE RESPIRATOR

KEY TECHNOLOGY



Proprietary
Foam Nose Seal



3 Panel
Construction



Fluid Resistant
Level 3 160 mmHg



Low Breathing
Resistance Filter

FEATURES

- Advanced multilayer technology providing protection against mechanically and thermally generated particulates including: fluids, dusts, mists, fumes and smoke
- Three panel design provides structural integrity, form fit seal and optimal comfort. All three mask panels and seams have been independently tested and certified to AS 4381:2015 Level 3 – ISO 22609
- Bacterial Filtration Efficiency (BFE) >99%
- Fluid protection level 3, 160 mmHg
- Proprietary adjustable foam nose pad to ensure consistent optimum facial seal and reduce fogging of eyewear
- Versatile unisex fit suitable for a vast range of facial shapes and sizes. Effective for many "hard to fit" individuals
- Specialised TRIDENT® respirator seal attains unrivalled PortaCount® fit testing results
- Low breathing resistance maximising wearer comfort, durability and life of product
- Designed to be used in conjunction with other mandatory personal protective equipment
- Latex free
- Each mask is individually batch numbered and packaged for the ultimate in traceability, portability and hygiene

AREAS OF APPLICATION

- Particulate Filtration
- Bacterial & Fluid Protection
- Personal Hygiene & Safety



Part No: **RTCFFP2**



SIZING


Extra Small	RTCFFP2XS
Small	RTCFFP2S
Regular	RTCFFP2
Regular Extended Length Head Straps	RTCFFP2E

PACKAGING

1 mask per bag
20 masks per inner
480 masks per carton

RTCFFP2XS	400 x 350 x 460mm GW: 5.9kg NW: 3.4kg
RTCFFP2S	440 x 390 x 460mm GW: 7.8kg NW: 4.5kg
RTCFFP2	630 x 250 x 580mm GW: 7.8kg NW: 4.5kg
RTCFFP2E	630 x 250 x 620mm GW: 7.8kg NW: 4.5kg

STORAGE



STANDARDS & CERTIFICATIONS



CERTIFIED P2
AS/NZS 1716: 2012
ID No. BMP 732382



AS 4381: 2015 Level 3
ID No. BMP 737354

ARTG
344154

A
CarbonZero®
Product



6 Precision Lane, Notting Hill, VIC 3168
<https://www.ausmedhealth.com.au/>
contact@ausmedhealth.com.au

