

HARALSON BELT BAG - Supplies and Class Preparation

SUPPLIES:

[The shop kit contains everything you need.](#)

If you are not purchasing the kit, you need the following:

[Haralson Belt Bag pattern](#)

Fabric Requirements - Please read the pattern too:

Exterior Fabric -midweight canvas or cotton twill:

If you are using one fabric, like the shop sample: 1/3 yard

If you are using an accent fabric on the flap: One fat quarter for the exterior AND
One fat quarter for the accent flap

Lining Fabric - quilting cotton: ½ yard or 1/3 yard directional fabric

Fusible Woven Interfacing – 1 ¾ yards, I used 20” wide [Pellon SF101](#), as suggested.

Zippers –pattern assumes zipper tape width of 1” to 1 ¼”.

EITHER one 8” zipper for back pocket, and one 6” zipper for interior pocket,

OR ½ yard continuous zipper with two zipper pulls

Hardware –

(2) 1” wide D rings;

(1) 1” wide strap slider; and

(1) 1” wide swivel snaps for strap hardware.

The above three items are all contained in [this hardware kit](#)

In class we are installing the turn lock closure option -

(1) [Turn lock](#)

BEFORE CLASS:

Cut fabric and interfacing as instructed on page 3-5 of the pattern.

Use the labels, and note that some pieces do get two layers of interfacing.

Fuse all pieces and layers as instructed, and bring all labeled pieces to class.

Webbing – cut two 2 1/2 “ pieces.

Do NOT cut the webbing further yet, as you may want leave your strap longer.

BRING TO CLASS:

Sewing machine with new microtex needle Size 14 or 16 denim

Thread and full bobbins for piecing and topstitching

Regular/piecing foot. I used my 1/4 " foot

Zipper foot

Chalk pen or water soluble pen

[Glue pen](#) (this is not an error)

Small cutting mat for next to your machine is helpful

Ruler

Rotary cutter with a sharp blade

Wonder clips and pins

Seam ripper (just in case 😊)