

Diesel Bulk Transfer Tanks

600 – 3000 LTRS - 12V



	DMP600	DMP800	DMP1200	DMP2000	DMP3000
Manufacturer	Polymaster Pty Ltd	Polymaster Pty Ltd	Polymaster Pty Ltd	Polymaster Pty Ltd	Polymaster Pty Ltd
Tank Type	Bulk Transfer Tank	Bulk Transfer Tank	Bulk Transfer Tank	Bulk Transfer Tank	Bulk Transfer Tank
Nominal Capacity (ltrs)	600	800	1200	2000	3000
Working Volume (ltrs)	600	800	1200	2000	3000
Tare Weight (kg)	57	77	92	107	142
Tank Material of Construction	Polyethylene - 7040	Polyethylene – 7040	Polyethylene – 7040	Polyethylene – 7040	Polyethylene - 7040
Overall Length (mm)	1200	1450	1450	1900	2100
Overall Width (mm)	1050	1200	1200	1450	1500
Overall Height (mm)	715	740	1000	1100	1200
Max. Specific Gravity Rating	1	1	1	1	1
Colour	Light Grey	Light Grey	Light Grey	Light Grey	Light Grey
Standard Fitting Specifications					
Fill Connection					
Size	DN50 M BSP	DN50 M BSP	DN50 M BSP	DN50 M BSP	DN50 M BSP
MOC/Type	Galvanised Fill Plate	Galvanised Fill Plate	Galvanised Fill Plate	Galvanised Fill Plate	Galvanised Fill Plate
Max Fill Rate (L/min)	N/A	N/A	N/A	N/A	N/A
Anti-Splash Fill Line	YES	YES	YES	YES	YES
Fill Plate Cap	DN50 F BSP	DN50 F BSP	DN50 F BSP	DN50 F BSP	DN50 F BSP
MOC/Type	Aluminium	Aluminium	Aluminium	Aluminium	Aluminium
Vent					
Size (mm)	25	25	25	25	25
MOC/Type	Aluminium W/ Gal Riser	Aluminium W/ Gal Riser	Aluminium W/ Gal Riser	Aluminium W/ Gal Riser	Aluminium W/ Gal Riser

The information provided in this document is general in nature and does not take into account your personal situation. You should consider whether the information is appropriate to your needs, and where appropriate, seek professional advice. Although every effort has been made to verify the accuracy of the information contained in this document, Polymaster, its officers, employees, and agents disclaim all liability (except for liability which by law cannot be excluded), for any error, inaccuracy in, or omission from the information contained in this document or any loss or damage suffered by any person directly or indirectly through relying on this information.



Suction Connection					
Size	DN25	DN25	DN25	DN25	DN25
MOC/Type	Steel Telescopic	Steel Telescopic	Steel Telescopic	Steel Telescopic	Steel Telescopic
Check Valve	Brass w/ Strainer	Brass w/ Strainer	Brass w/ Strainer	Brass w/ Strainer	Brass w/ Strainer
Pump					
Make	Piusi	Piusi	Piusi	Piusi	Piusi
Model	NT0007024	NT0007024	NT0007024	NT0007024	NT0007024
Phase	DC	DC	DC	DC	DC
Voltage (V)	12	12	12	12	12
Flow Rate (L/min)	45	45	45	45	45
IP Rating	IP55	IP55	IP55	IP55	IP55
Outlet					
Size	DN20	DN20	DN20	DN20	DN20
Type	Automatic Trigger Nozzle	Automatic Trigger Nozzle	Automatic Trigger Nozzle	Automatic Trigger Nozzle	Automatic Trigger Nozzle
Volume (L/min)	65	65	65	65	65
Hose					
Length (Meters)	4	4	4	4	4
Size	DN20	DN20	DN20	DN20	DN20
MOC	PVC - Diesel Grade	PVC - Diesel Grade	PVC - Diesel Grade	PVC - Diesel Grade	PVC - Diesel Grade
Static Lead					
Length (Meters)	2	2	2	2	2
Connection	Alligator Clip	Alligator Clip	Alligator Clip	Alligator Clip	Alligator Clip
Static Lead Must be Connected for Safe Operation and Compliance with Worksafe Approval.					

Optional Fitting Specifications					
Fast Flow Pump Kit	DMPF600	DMPF800	DMPF1200	DMPF2000	DMPF3000
Make	Piusi	Piusi	Piusi	Piusi	Piusi
Model	NT0007024	NT0007024	NT0007024	NT0007024	NT0007024
Phase	DC	DC	DC	DC	DC
Voltage (V)	12	12	12	12	12
Flow Rate (L/min)	85	85	85	85	85
IP Rating	IP55	IP55	IP55	IP55	IP55

The information provided in this document is general in nature and does not take into account your personal situation. You should consider whether the information is appropriate to your needs, and where appropriate, seek professional advice. Although every effort has been made to verify the accuracy of the information contained in this document, Polymaster, its officers, employees, and agents disclaim all liability (except for liability which by law cannot be excluded), for any error, inaccuracy in, or omission from the information contained in this document or any loss or damage suffered by any person directly or indirectly through relying on this information.



Outlet					
Size	DN25	DN25	DN25	DN25	DN25
Type	Automatic Trigger Nozzle	Automatic Trigger Nozzle	Automatic Trigger Nozzle	Automatic Trigger Nozzle	Automatic Trigger Nozzle
Volume (L/min)	90	90	90	90	90
Hose					
Length (Meters)	4	4	4	4	4
Size	DN25	DN25	DN25	DN25	DN25
MOC	PVC - Diesel Grade	PVC - Diesel Grade	PVC - Diesel Grade	PVC - Diesel Grade	PVC - Diesel Grade

Dual Voltage Pump Kit	DMPD600	DMPD800	DMPD1200	DMPD2000	DMPD3000
Make	Piusi	Piusi	Piusi	Piusi	Piusi
Model	F0034100C	F0034100C	F0034100C	F0034100C	F0034100C
Phase	DC	DC	DC	DC	DC
Voltage (V)	12/24	12/24	12/24	12/24	12/24
Flow Rate (L/min)	35/70	35/70	35/70	35/70	35/70
IP Rating	IP55	IP55	IP55	IP55	IP55
Outlet					
Size	DN20	DN20	DN20	DN20	DN20
Type	Automatic Trigger Nozzle	Automatic Trigger Nozzle	Automatic Trigger Nozzle	Automatic Trigger Nozzle	Automatic Trigger Nozzle
Volume (L/min)	65	65	65	65	65
Hose					
Length (Meters)	4	4	4	4	4
Size	DN20	DN20	DN20	DN20	DN20
MOC	PVC - Diesel Grade	PVC - Diesel Grade	PVC - Diesel Grade	PVC - Diesel Grade	PVC - Diesel Grade

The information provided in this document is general in nature and does not take into account your personal situation. You should consider whether the information is appropriate to your needs, and where appropriate, seek professional advice. Although every effort has been made to verify the accuracy of the information contained in this document, Polymaster, its officers, employees, and agents disclaim all liability (except for liability which by law cannot be excluded), for any error, inaccuracy in, or omission from the information contained in this document or any loss or damage suffered by any person directly or indirectly through relying on this information.

