

## **AUSSIE QUIK PRIME DIESEL DRIVE TRASH PUMPS**

Rugged trash pumps in 2", 3" and 4" with flows to 1800 litres per minute, heads to 27 metres and suction lift to 7.6 metres.

Aussie QP Yanmar powered trash pumps feature unique mechanical seals that outlast conventional seals by up to six times.

#### Features

- Five year pump warranty
- Big non clog open style impeller
- High SG grade cast iron impeller volute
- Front mounted clean out port
- Super robust aluminium body
- Full carry frame
- Yanmar or Kubota diesel engines (two year engine warranty)
- Coupling and strainer kit included as standard options
- Honda petrol drive options available (see separate spec sheet)

#### Specifications

Max solid Model Engine Engine model ΗP Max Head Max Flow Suction port Discharge port Self primes to Brand size (m) (lpm) (m) QP203T L48 or L48E 2″ 0.75" Yanmar 4.8 27 600 2" 7.3 QP300T Yanmar L48 or L48E 4.8 27 850 3″ 3″ 7.4 0.75" QP301T Yanmar L70, L70E, L100E 7.0, 10 24 1150 3″ 3″ 7.5 1″ 4″ QP40T L100E 10 24 1800 4″ 7.6 Yanmar 1.5'

NOTE: Aussie stock codes for QP pumps are determined by using the pump & engine model, for example QP301T/L70E is the 7HP Yanmar, electric start version of the QP301T


#### **Five Year Warranty:**

Aussie Quik Prime pumps carry a unique pump end five year warranty. The products are guaranteed to be free of faulty workmanship or material for a period of five years after the date of sale to the end user.

Only top quality genuine brand engines by reputable manufacturers are used. A 2 year Yanmar engine warranty applies, administered by the Yanmar international service network.

Due to our program of continuous product development the manufacturer reserves the right to alter specifications without notice.

Australian Pump Industries Pty Ltd | 7 Gladstone Road, Castle Hill NSW 2154 | P: 02 8865 3500 | F: 02 9894 4240 | www.aussiepumps.com.au




The high SG, cast iron, non clog style, open impeller and volute system is designed to pump solids and resist wear.

#### Benefits

- » Great quality ... use with confidence
- Pumps solids in suspension »
- Resists wear and abrasion »
- Makes pump chamber clearance easy, no » dismantling of pump body or pipe work
- Corrosion resistant, long life »
- Protects pump, facilitates transport on site »
- Tried and proven with established service » networks throughout the world
- Prevents oversized material entering pump »
- Convenience and cost savings





- Construction site dewatering
- Waste water handling
- Effluent pump out
- Livestock waste water disposal
- Solid laden mine waste pump out

# Frame Options:

Standard

- Site Boss configuration ... Super robust gal frame with integrated lifting bar (see page 3)
- Mine Boss configuration ... additional safety features for use in mining applications (see page 3)





## AUSSIE QUIK PRIME DIESEL DRIVE TRASH PUMPS

#### **Construction:**

Front case	Marine grade aluminium
Volute	High SG grade cast iron
Back plate	Marine grade aluminium
Mechanical seal	Silicon carbide
Outlet	Marine grade aluminium
Casing bolts	Zinc plated steel
Check valve	Nitrile rubber
Priming & drain plugs	Polycarbonate
Casing, priming & drain plug o-rings	Nitrile rubber
Finish	Brushed aluminium (except QP40T)
Impeller	High SG grade cast iron, non clog, open type

Aussie Dumps

QP40T MS .. Mine Boss configuration (see page 3)


**Standard Accessories:** 


Full frame

Coupling kit & strainer

YANMAR


### **Dimensions:**





Model	Engine	A Width (mm)	B Height (mm)	C Length (mm)	Weight (kg)
QP203T recoil	L48	420	681	630	65
e/start	L48E	544	681	630	75
QP300T recoil	L48	420	681	630	65
e/start	L48E	544	681	630	75
QP301T e/start	L100E	618	661	735	90
QP40T e/start	L100E	655	740	721	115

#### **Performance Curve:**



#### **Optional Accessories:**

- Heavy duty suction hose
- Medium pressure lay flat delivery hose
- Camlock couplings
- Hydraulic drive option



Due to our program of continuous product development the manufacturer reserves the right to alter specifications without notice.

Australian Pump Industries Pty Ltd | 7 Gladstone Road, Castle Hill NSW 2154 | P: 02 8865 3500 | F: 02 9894 4240 | www.aussiepumps.com.au



## **AUSSIE QUIK PRIME DIESEL DRIVE TRASH PUMPS**

## **QP MINE BOSS TRASH PUMPS ... MADE AUSSIE MINE TOUGH**

- Yanmar electric start diesel engines with 2 year warranty
- 5 year pump end warranty
- QP trash pump
- Fast self priming from 7.6m
- Aussie Mine Boss trash pumps includes following safety features
- Balanced lifting bar
- **Emergency stop**
- Gel battery

- Replaceable flanged suction port
- 38mm super robust gal frame with lifting bar & anti vibration mounts
- Marine grade aluminium pump body
- FREE coupling & strainer kit
- Trolley mount option

- Lockable battery isolation Integrated fire extinguisher
- Hi vis stickers

Aussic Du P203T M

# YANMAR

Model	Engine Brand	Engine model	HP	Max Head (m)	Max Flow (Ipm)	Suction port	Discharge port	Self primes to (m)	Max solid size	Carton size (mm) Ixwxh	Boxed weight kg
QP203T MS	Yanmar	L48E	4.8	27	600	2″	2″	7.3	0.75″	600x680x660	95
QP300T MS	Yanmar	L48E	4.8	27	850	3″	3″	7.4	0.75″	600x680x660	95
QP301T MS	Yanmar	L100E	10.0	24	1200	3″	3″	7.5	1″	810x605x870	120
QP40T MS	Yanmar	L100E	10.0	24	1800	4"	4"	7.6	1.5″	810x605x870	135

## **QP SITE BOSS TRASH PUMPS ... RUGGED, FOR EASY LIFTING**

- Yanmar electric start diesel engines with 2 year warranty
- 5 year pump end warranty
- QP trash pump
- Fast self priming from 7.6m
- Replaceable flanged suction port
- 38mm super robust gal frame with lifting bar & anti vibration mounts
- Marine grade aluminium pump body
- FREE coupling & strainer kit



Model	Engine Brand	Engine model	HP	Max Head (m)	Max Flow (Ipm)	Suction port	Discharge port	Self primes to (m)	Max solid size	Carton size (mm) lxwxh	Boxed weight kg
QP203T SB	Yanmar	L48E	4.8	27	600	2″	2″	7.3	0.75″	600x680x660	85
QP300T SB	Yanmar	L48E	4.8	27	850	3″	3″	7.4	0.75″	600x680x660	85
QP301T SB	Yanmar	L100E	10.0	24	1200	3″	3″	7.5	1″	810x605x870	110
QP40T SB	Yanmar	L100E	10.0	24	1800	4"	4"	7.6	1.5″	810x605x870	125

Due to our program of continuous product development the manufacturer reserves the right to alter specifications without notice.

Australian Pump Industries Pty Ltd | 7 Gladstone Road, Castle Hill NSW 2154 | P: 02 8865 3500 | F: 02 9894 4240 | www.aussiepumps.com.au