turbo twister

by essentials TM



PROFESSIONAL SPRAY TANNING FILTER SYSTEM

WELCOME

Thank you for choosing a Tanning Essentials Professional Spray Tan Filter System. Please read the following to enjoy your new system for many happy tanning applications.

QUICK SET UP GUIDE

The Profession Spray Tanning Filter System contains the following:

- 2 x Fan Unit
- 1 x Top Unit
- 1 x Base Unit
- 2 x Sides Panels
- 1 x Rubber Floor
- 2 x Steel Rails
- 1 x Connection Cord
- 1 x Foot Pedal Power Cord
- 14 x Screws



IMPORTANT

Please keep your proof of Purchase and User Manual in a safe place as you will require these to make a warranty claim. Prior to making a claim you should read through the trouble shooting section in the manual and contact your supplier via phone. Any warranty claims should be made directly to your supplier.

If, within one (1) year from the date of purchase, the product fails due to a defect in material or workmanship, we will repair if possible or replace it free of charge with a comparable unit which may be new or refurbished. This warranty applies only to the original purchaser and is not transferable. The goods must be returned to the seller with proof of purchase to be assessed at the purchasers cost.

Warranties shall not apply to any defect, failure or damage caused by improper use or improper or inadequate maintenance and care. The manufacturer shall not be obligated under these warranties:


- a) to repair damage resulting from attempts by personnel other than authorised representatives to install, repair or service the product,
- b) to repair damage, malfunction, or degradation of performance resulting from improper use or incompatible solution,
- c) to perform maintenance or cleaning or to repair damage, malfunction, or degradation of performance resulting from failure to perform user maintenance and cleaning as prescribed,
- d) to repair damage, malfunction, or degradation of performance resulting from use of the product in an environment not meeting the operating specifications,

To activate your warranty, please complete the information below and post to your supplier within 14 days of purchase.

ASSEMBLY INSTRUCTION



STEP 1Lay rubber floor into position



STEP 2Place Base on rubber floor



STEP 3Stack fan units on top of the base



STEP 4Attach metal rails to the base and fan units using the screws.



Note: only loosely screw the rails into position, allowing room to insert the sides and only tighten after the sides are in place.



STEP 5Complete the tower ensuring the top unit is located at the top



STEP 6Insert the sides between the units and rails, starting at the top, clamping them tightly once in position.



STEP 7Connect the fan unit by the cord and attach the foot pedal

CHANGING THE FILTER

Loosen the screws on all the units and remove the top filter cover first

The filters are disposable and replacement filters are ordered in a 2 pack and recommended to be changed after 100+ sprays.





