

EASY FLOW

1 component water-based PU acrylate for parquet and wooden surfaces. Gives a clear protection to the wood. Easy to use, universal and neutral in overlaps

- » Good application properties.
- » Easy to apply
- » Good chemical and mechanical resistance

TECHNICAL DATA

Product type

waterborne

Cleaning

water

Gloss level

Matt 15

Satin 40

Viscosity

+/-25 sec - DIN 4mm

Solids content

+/- 31%

Packaging

4 x 5 L

Coverage

10-12 m²/liter per coat

100-130 sq.ft./L per coat

Drying times

Dust dry: after 20 to 30 minutes

Sandable: after 4 to 6 hours

Load-bearing: after 24 hours

Fully cured: after +/- 7 days

Sanding grit

P 120-150

Storage/transport

between 5°C and 25°C

Shelf life

12 months in the original and unopened packaging.

Disposal

Dispose of residue and empty packaging in accordance with local ordinances.



5L



PREPARATION

Make sure all prior coatings are completely removed and the wood surface is free from dust and other contamination. Can be used on sanded, planed and brushed wood. For under-floor heating, exotic wood and cork, FORTICO sealer is recommended as primer.

APPLICATION

Use EASY FLOW 1C as a primer and finishing coat. Apply the product by brush or roller in 3 coats.

First coat: apply approx. 80-100 g/m² and leave to dry for approx. 4 hours. Second coat: apply approx. 80-100 g/m² in the same manner as the first coat and leave to dry for +/- 6 hours. Before applying the 3th coat intermediate sanding with 180-220 grain, remove dust and apply the third coat approx. 80-100 g/m².

DRYING TIMES

Recoat time: 2-3 hours between coats Light foot traffic is acceptable after 24 hours Allow one week before exposing finish to rugs, cleaners, spills or heavy traffic. Drying times are dependent on the applied quantity, temperature, humidity and ventilation.

MAINTENANCE

Regular maintenance with Hard Floor Fresh Ciranova®. Use UNICARE X-MATT or Hard floor Polish for periodic maintenance. Hard Floor Cleaner Ciranova® is used for cleaning highly soiled; floors and to remove old layers of polish.

IMPORTANT INFORMATION ⚠

Only use corrosion-resistant materials. Clean all materials with water immediately after use. For industrial applications, consult Ciranova® technical services. **Once the package is opened, skin formation is possible after contact with air, filter before use.**