



Burke Wall Base

Mannington
COMMERCIAL



Cover: BurkeBase® - 204 Gray (ACCORD color), Confluence Modular Carpet - Optimism 81010, Security 63014 (Installation - Vertical Ashlar)
Above: BurkeBase® - 820 Daffodil, Abstracted Strie LVT - Core ANT400



Accord Colors

The Accord System offers 36 color choices that span the entire spectrum of premium rubber flooring products, including wall base, tiles, stair treads and finishing accessories.

TS Vulcanized Thermoset Rubber, TP Coextruded Thermoplastic Vinyl, and TV Coextruded Thermoplastic Vinyl

| Wall Base Type | 2.5" x .080" toeless & coved | 2.5" x 1/8" toeless & coved | 4" x .080" toeless & coved | 4" x 1/8" toeless & coved | 4.5" x 1/8" toeless & coved | 6" x .080" toeless & coved | 6" x 1/8" toeless & coved | 10" x 1/8" toeless only | 4' lengths toeless & coved | 100' seamless rolls toeless & coved | 100 color offering (includes 36 Accord colors) | 4" x 1/8" coved (10 colors) 6" x 1/8" coved (black only) |
|-----------------|------------------------------|-----------------------------|----------------------------|---------------------------|-----------------------------|----------------------------|---------------------------|-------------------------|----------------------------|-------------------------------------|--|---|
| Type TV - Matte | * | * | * | * | * | * | * | | * | * | * | |
| Type TP - Matte | | * | | * | * | | * | | * | * | * | |
| Type TS - Satin | | | | | | | | | | select colors, coved only | | * |

* Some limitations in availability - see spec page for full details. Inside and outside corners also available.

Custom colors available for a minimum.

| | | | | | |
|---|---|---|--|---|---|
|  |  |  |  |  |  |
| Almond 403 | Off White 244 | Beach Sand 030 | Light Gray 208 | Frosted Jade 210 | Mocha 597 |
|  |  |  |  |  |  |
| Cream 205 | Baja 519 | Sky Gray 663 | Carmine Gray 674 | Daffodil 820 | Mango 070 |
|  |  |  |  |  |  |
| Desert Sand 118 | Gray Beige 209 | Jackalope 190 | Ash 603 | Sugar Snap 055 | Geranium 966 |
|  |  |  |  |  |  |
| Ginger 503 | Sandy Tan 112 | Gray 204 | Gray Blue 672 | Mountain Meadow 077 | Peacock 120 |
|  |  |  |  |  |  |
| Tumbleweed 033 | Clay 527 | Moonbeam 050 | Rocky 660 | Dark Forest 331 | Ocean Blue 115 |
|  |  |  |  |  |  |
| Pecan 504 | Brown 502 | BlackBrown 523 | Charcoal 217 | Black 701 | Navy 875 |

Performance and Features

| Available Heights/Sizes | BurkeBase Type TS 1/8" * | BurkeBase Type TP 1/8" ** | BurkeBase Type TV 1/8" ** | BurkeBase Type TV .080" ** |
|-------------------------|-----------------------------|------------------------------|------------------------------|-------------------------------|
| | 4" (102 mm) | 2.5" (64 mm) | 2.5" (64 mm) | 2.5" (64 mm) |
| | 6" (152 mm) | 4" (102 mm) | 4" (102 mm) | 4" (102 mm) |
| | | 4.5" (114 mm) | 4.5" (114 mm) | 6" (152 mm) |
| | | 6" (152 mm) | 6" (152 mm) | |
| | Coved | Coved or Toeless | Coved or Toeless | Coved or Toeless |

Warranty This product is backed by our Limited 5 Year Commercial Warranty.

Corners BurkeBase® Type TS factory molded corners are available in all profile sizes except 10" and toeless corners. Must be ordered at time of wall base order to ensure color match.

BurkeBase® Type TP/TV pre-formed corners are available in all profile sizes. Must be ordered at time of wall base order to ensure color match.

Custom Colors Minimums apply.

Please make final selection for all colors from actual product samples.
For samples and information visit manningtoncommercial.com or call 800.241.2262.

Thermoset Rubber

BurkeBase® Rubber Wall Base
Type TS Benefits

- Vulcanized thermoset rubber to prevent shrinkage or expansion
- Molded to provide dimensional stability
- Smooth satin finish and inherent flexibility helps hide substrate irregularities
- Available in 4' molded lengths
- 4" (10 Colors), 6" (Black only)

Thermoplastic Rubber

BurkeBase® Rubber Wall Base
Type TP Benefits

- Heavy gauge rubber base
- Flexible formulation easily forms to curves and corners for clean installation
- Will not fade or crack
- Scuff and scratch resistant
- Available in 4' lengths and 100' seamless rolls
- 100 standard colors including 36 ACCORD colors

Vinyl

BurkeBase® Vinyl Wall Base
Type TV Benefits

- Engineered for heavy traffic and high maintenance areas
- Scuff and abrasion resistant
- Tough matte finish helps hide substrate irregularities
- Available in .080" and .125" gauges
- Available in 4' lengths and 100' seamless rolls
- 100 standard colors including 36 ACCORD colors

* Type TP & TV Coved and Toeless 4' lengths & 100' rolls available in 2.5", 4", 4.5", and 6" heights. Both available in .080" & 1/8" thickness.

| Style | BurkeBase Type TS 1/8" * | BurkeBase Type TP 1/8" ** (Non-Ortho Phthalate) |
|---|---|---|
| Construction | Thermoset Rubber | Thermoplastic Rubber |
| Finish | Satin | Matte |
| Classification | ASTM F1861 Type TS, Group 1 | ASTM F1861 Type TP, Group 1 |
| Total Thickness | 1/8" (3.2 mm) | 1/8" (3.2 mm) |
| Profile | Coved 4" (102 mm) 6" (Black Only) (152 mm) | Coved or Toeless 2.5" (64 mm) 4" (102 mm) 4.5" (114 mm) 6" (152 mm) |
| Colors | 10 | 100 (36 are Accord) |
| Packaging | 25-4' pieces = 100' per carton | 1-100' continuous roll or 25-4' pieces |
| Weight Per Carton – 2.5" / 4" / 4.5" / 6" / 10" | Coved = 39/53 lbs. | Coved = 25/38/41/53 lbs. Toeless = 24/35/41/52 lbs. |
| Weight Per Carton – Corners | Coved = 4/7 lbs. | Coved = 3/4/9 lbs. Coved = 3/4/9 lbs. |
| Corners (must be ordered at time of wall base order to ensure color match) | Factory molded corners available | Factory pre-formed corners available |
| Adhesive | Burke BR-101 | Burke BR-101 |
| Testing | | |
| Static Load (ASTM E970) | 500 psi | |
| Flooring Radiant Panel (ASTM E648) | Passes - Class I; ≥ 0.45 watts/cm2 | |
| Smoke Density (ASTM E662) | Passes - < 450 | |
| Environmental Data | | |
| Indoor Air Quality | FloorScore Certified | |
| LEED Scoreboard | May contribute to LEED and Green Globes credits LEED 2009: MRc5 Regional Material; IEQ4.1 Low Emitting Adhesives; IEQ4.3 Low Emitting Materials - Flooring LEEDv4: IEQc2 - Low Emitting Materials | |
| Manufacturing | Calhoun, GA USA | |
| Warranty | | |
| | Limited 5 Year Commercial Warranty | |

- Maintain a minimum temperature in the spaces to receive the wall base and accessories of 65°F (18°C) and a maximum temperature of 85°F (29°C) for at least 48 hours before, during and for not less than 48 hours after installation. Thereafter, maintain a minimum temperature of 55°F (13°C) in areas where work is completed. Dirt, wetness and improper maintenance may cause significant variation in actual performance. Such variations do not affect product performance.
- Specifications are based on averages from normal manufacturing tolerances.
- This product is intended solely for use indoors and is not recommended or sold for any other purpose.

* Type TS Coved and Toeless 4' lengths available in 2.5', 4', 6', and 10" (10" heights - 1/8" toeless ONLY). Type TS 100' rolls are only available in these ten colors: 204, 206, 208, 209, 217, 502, 523, 597, 701 and 727 in 4" height only.

** Type TP & TV Coved and Toeless 4' lengths & 100' rolls available in 2.5', 4', 4.5', and 6" heights. Both available in .080 & 1/8" thickness.

Crafted with purpose

| Style | BurkeBase Type TV 1/8" ** (Non-Ortho Phthalate) | BurkeBase Type TV .080" ** (Non-Ortho Phthalate) |
|--|---|--|
| Construction | Vinyl | Vinyl |
| Finish | Matte | Matte |
| Classification | ASTM F1861 Type TV, Group 1 | ASTM F1861 Type TV, Group 1 |
| Total Thickness | 1/8" (3.2 mm) | .080" (2.0 mm) & 1/8" (3.2 mm) |
| Profile | Coved or Toeless | Coved or Toeless |
| Sizes | 2.5" (64 mm) 4" (102 mm) 4.5" (114 mm) 6" (152 mm) | 2.5" (64 mm) 4" (102 mm) 6" (152 mm) |
| Colors | 100 (36 are Accord) | 100 (36 are Accord) |
| Packaging | 1-100' continuous roll or 25-4' pieces | 1-100' continuous roll or 25-4' pieces |
| Weight Per Carton – 2.5" / 4" / 4.5" / 6" / 10" | Coved (1/8") = 24/37/41/53 lbs. Toeless (1/8") = 23/36/41/52 lbs. | Coved (.080") = 19/27/41/42 lbs. Toeless (.080") = 17/25/41/39 lbs. |
| Weight Per Carton – Corners | Coved = 3/4/9 lbs. Toeless = 3/4/9 lbs. | Coved (.080") = 3/3/8 lbs. Toeless (.080") = 2/3/7 lbs. |
| Corners (must be ordered at time of wall base order to ensure color match) | Factory pre-formed corners available | Factory pre-formed corners available |
| Adhesive | Burke BR-101 | Burke BR-101 |
| Testing | | |
| Static Load (ASTM E970) | 500 psi | |
| Flooring Radiant Panel (ASTM E648) | Passes - Class I; ≥ 0.45 watts/cm2 | |
| Smoke Density (ASTM E662) | Passes - < 450 | |
| Environmental Data | | |
| Indoor Air Quality | FloorScore Certified | |
| LEED Scoreboard | May contribute to LEED and Green Globes credits LEED 2009: MRc5 Regional Material; IEQ4.1 Low Emitting Adhesives; IEQ4.3 Low Emitting Materials - Flooring LEEDv4: IEQc2 - Low Emitting Materials | |
| Manufacturing | Calhoun, GA (USA) | |
| Warranty | | |
| | Limited 5 Year Commercial Warranty | Limited 5 Year Commercial Warranty |

- Maintain a minimum temperature in the spaces to receive the wall base and accessories of 65°F (18°C) and a maximum temperature of 85°F (29°C) for at least 48 hours before, during and for not less than 48 hours after installation. Thereafter, maintain a minimum temperature of 55°F (13°C) in areas where work is completed. Dirt, wetness and improper maintenance may cause significant variation in actual performance. Such variations do not affect product performance.
- Specifications are based on averages from normal manufacturing tolerances.
- This product is intended solely for use indoors and is not recommended or sold for any other purpose.

* Type TS Coved and Toeless 4' lengths available in 2.5', 4', 6', and 10" (10" heights - 1/8" toeless ONLY). Type TS 100' rolls are only available in these ten colors: 204, 206, 208, 209, 217, 502, 523 and 597 in 4" height only.

** Type TP & TV Coved and Toeless 4' lengths & 100' rolls available in 2.5', 4', 4.5", and 6" heights. Both available in .080 & 1/8" thickness.