

| Style | BurkeBase Type TS 1/8" * | BurkeBase Type TP 1/8" ** (Non-Ortho Phthalate) |
|---|---|---|
| Construction | Thermoset Rubber | Thermoplastic Rubber |
| Finish | Satin | Matte |
| Classification | ASTM F1861 Type TS, Group 1 | ASTM F1861 Type TP, Group 1 |
| Total Thickness | 1/8" (3.2 mm) | 1/8" (3.2 mm) |
| Profile | Coved 4" (102 mm) 6" (Black Only) (152 mm) | Coved or Toeless 2.5" (64 mm) 4" (102 mm) 4.5" (114 mm) 6" (152 mm) |
| Colors | 10 | 100 (36 are Accord) |
| Packaging | 25-4' pieces = 100' per carton | 1-100' continuous roll or 25-4' pieces |
| Weight Per Carton – 2.5" / 4" / 4.5" / 6" / 10" | Coved = 39/53 lbs. | Coved = 25/38/41/53 lbs. Toeless = 24/35/41/52 lbs. |
| Weight Per Carton – Corners | Coved = 4/7 lbs. | Coved = 3/4/9 lbs. Coved = 3/4/9 lbs. |
| Corners (must be ordered at time of wall base order to ensure color match) | Factory molded corners available | Factory pre-formed corners available |
| Adhesive | Burke BR-101 | Burke BR-101 |
| Testing | | |
| Static Load (ASTM E970) | 500 psi | |
| Flooring Radiant Panel (ASTM E648) | Passes - Class I; ≥ 0.45 watts/cm2 | |
| Smoke Density (ASTM E662) | Passes - < 450 | |
| Environmental Data | | |
| Indoor Air Quality | FloorScore Certified | |
| LEED Scoreboard | May contribute to LEED and Green Globes credits LEED 2009: MRc5 Regional Material; IEQ4.1 Low Emitting Adhesives; IEQ4.3 Low Emitting Materials - Flooring LEEDv4: IEQc2 - Low Emitting Materials | |
| Manufacturing | Calhoun, GA USA | |
| Warranty | | |
| | Limited 5 Year Commercial Warranty | |

- Maintain a minimum temperature in the spaces to receive the wall base and accessories of 65°F (18°C) and a maximum temperature of 85°F (29°C) for at least 48 hours before, during and for not less than 48 hours after installation. Thereafter, maintain a minimum temperature of 55°F (13°C) in areas where work is completed. Dirt, wetness and improper maintenance may cause significant variation in actual performance. Such variations do not affect product performance.
- Specifications are based on averages from normal manufacturing tolerances.
- This product is intended solely for use indoors and is not recommended or sold for any other purpose.

* Type TS Coved and Toeless 4' lengths available in 2.5', 4', 6', and 10" (10" heights - 1/8" toeless ONLY). Type TS 100' rolls are only available in these ten colors: 204, 206, 208, 209, 217, 502, 523, 597, 701 and 727 in 4" height only.

** Type TP & TV Coved and Toeless 4' lengths & 100' rolls available in 2.5', 4', 4.5', and 6" heights. Both available in .080 & 1/8" thickness.

Crafted with purpose

| Style | BurkeBase Type TV 1/8" ** (Non-Ortho Phthalate) | BurkeBase Type TV .080" ** (Non-Ortho Phthalate) |
|--|---|--|
| Construction | Vinyl | Vinyl |
| Finish | Matte | Matte |
| Classification | ASTM F1861 Type TV, Group 1 | ASTM F1861 Type TV, Group 1 |
| Total Thickness | 1/8" (3.2 mm) | .080" (2.0 mm) & 1/8" (3.2 mm) |
| Profile | Coved or Toeless | Coved or Toeless |
| Sizes | 2.5" (64 mm) 4" (102 mm) 4.5" (114 mm) 6" (152 mm) | 2.5" (64 mm) 4" (102 mm) 6" (152 mm) |
| Colors | 100 (36 are Accord) | 100 (36 are Accord) |
| Packaging | 1-100' continuous roll or 25-4' pieces | 1-100' continuous roll or 25-4' pieces |
| Weight Per Carton – 2.5" / 4" / 4.5" / 6" / 10" | Coved (1/8") = 24/37/41/53 lbs. Toeless (1/8") = 23/36/41/52 lbs. | Coved (.080") = 19/27/41/42 lbs. Toeless (.080") = 17/25/41/39 lbs. |
| Weight Per Carton – Corners | Coved = 3/4/9 lbs. Toeless = 3/4/9 lbs. | Coved (.080") = 3/3/8 lbs. Toeless (.080") = 2/3/7 lbs. |
| Corners (must be ordered at time of wall base order to ensure color match) | Factory pre-formed corners available | Factory pre-formed corners available |
| Adhesive | Burke BR-101 | Burke BR-101 |
| Testing | | |
| Static Load (ASTM E970) | 500 psi | |
| Flooring Radiant Panel (ASTM E648) | Passes - Class I; ≥ 0.45 watts/cm2 | |
| Smoke Density (ASTM E662) | Passes - < 450 | |
| Environmental Data | | |
| Indoor Air Quality | FloorScore Certified | |
| LEED Scoreboard | May contribute to LEED and Green Globes credits LEED 2009: MRc5 Regional Material; IEQ4.1 Low Emitting Adhesives; IEQ4.3 Low Emitting Materials - Flooring LEEDv4: IEQc2 - Low Emitting Materials | |
| Manufacturing | Calhoun, GA (USA) | |
| Warranty | | |
| | Limited 5 Year Commercial Warranty | Limited 5 Year Commercial Warranty |

- Maintain a minimum temperature in the spaces to receive the wall base and accessories of 65°F (18°C) and a maximum temperature of 85°F (29°C) for at least 48 hours before, during and for not less than 48 hours after installation. Thereafter, maintain a minimum temperature of 55°F (13°C) in areas where work is completed. Dirt, wetness and improper maintenance may cause significant variation in actual performance. Such variations do not affect product performance.
- Specifications are based on averages from normal manufacturing tolerances.
- This product is intended solely for use indoors and is not recommended or sold for any other purpose.

* Type TS Coved and Toeless 4' lengths available in 2.5', 4', 6', and 10" (10" heights - 1/8" toeless ONLY). Type TS 100' rolls are only available in these ten colors: 204, 206, 208, 209, 217, 502, 523 and 597 in 4" height only.
 ** Type TP & TV Coved and Toeless 4' lengths & 100' rolls available in 2.5', 4', 4.5", and 6" heights. Both available in .080 & 1/8" thickness.