



---

Edge Effects® Collection

**Mannington**  
COMMERCIAL



Cover: **Cetera** - Beach Sand 030, **Montgomery** (Broadloom) - Stirling 14113  
Above: **Etched** - White 401, **Intersect** - Foundation PD111



**Simplicity** - Sea Green 088, Uninterrupted Wood - Heartwood Oak UN204  
Pre-mitered inside and outside corners are available to match various wall base heights.

## Edge Effects® Sculptured Wall Base Packaging

Style	Total Thickness	Roll LF per Carton	Roll Carton Weight	8' Lengths Pcs per Carton	8' Lengths LF per Carton	8' Lengths Carton Weight	Inside/Outside Corners Pcs per Carton	Carton Weight
Cache (3")	3/8"	50 lf (15.24 m)	23 lbs (10.43 kg)	8	64 lf (19.51 m)	33 lbs (14.97 kg)	20	5 lbs (2.268 kg)
Cache (4 1/4")	3/8"	n/a	n/a	8	64 lf (19.51 m)	51 lbs (23.13 kg)	20	8 lbs (3.629 kg)
Cetera (4")	5/16"	36 lf (10.97 m)	44 lbs (19.96 kg)	6	48 lf (14.63 m)	59 lbs (26.76 kg)	20	14 lbs (6.35 kg)
Cetera (4 1/2")	5/16"	36 lf (10.97 m)	44 lbs (19.96 kg)	6	64 lf (19.51 m)	81 lbs (36.74 kg)	20	16 lbs (7.257 kg)
Corner Guard (1")	1/4"	n/a	n/a	20	160 lf (48.77 m)	40 lbs (18.14 kg)	n/a	n/a
Double Etched (4")	1/4"	50 lf (15.24 m)	44 lbs (19.96 kg)	8	64 lf (19.51 m)	57 lbs (25.85 kg)	20	9 lbs (4.082 kg)
Double Etched (4 1/4")	1/4"	50 lf (15.24 m)	45 lbs (20.41 kg)	8	64 lf (19.51 m)	61 lbs (27.67 kg)	20	10 lbs (4.536 kg)
Effectual Chair Rail (4")*	1/4"	n/a	n/a	5	60 lf (18.29 m)	46 lbs (20.87 kg)	n/a	n/a
Elegance (6")	3/16"	36 lf (10.97 m)	43 lbs (19.5 kg)	4	32 lf (9.754 m)	43 lbs (19.5 kg)	20	18 lbs (8.165 kg)
Etched (4")	1/4"	50 lf (15.24 m)	44 lbs (19.96 kg)	8	64 lf (19.51 m)	57 lbs (25.85 kg)	20	9 lbs (4.082 kg)
Etched (4")	3/8"	n/a	n/a	8	64 lf (19.51 m)	57 lbs (25.85 kg)	20	9 lbs (4.082 kg)
Etched (4 1/4")	1/4"	50 lf (15.24 m)	47 lbs (21.32 kg)	8	64 lf (19.51 m)	63 lbs (28.58 kg)	20	10 lbs (4.536 kg)
Etched (6")	1/4"	36 lf (10.97 m)	57 lbs (25.85 kg)	4	32 lf (9.754 m)	54 lbs (24.49 kg)	20	24 lbs (10.89 kg)
Flair (3")	5/16"	50 lf (15.24 m)	38 lbs (17.24 kg)	8	64 lf (19.51 m)	52 lbs (23.59 kg)	20	9 lbs (4.082 kg)
Iconic (4 1/4")	3/8"	n/a	n/a	8	64 lf (19.51 m)	53 lbs (24.04 kg)	20	9 lbs (4.082 kg)
Illusion (3 1/4")	3/8"	n/a	n/a	8	64 lf (19.51 m)	57 lbs (25.85 kg)	20	9 lbs (4.082 kg)
Lunar (4")	5/16"	36 lf (10.97 m)	43 lbs (19.5 kg)	8	64 lf (19.51 m)	77 lbs (34.93 kg)	20	14 lbs (6.35 kg)
Lunar (4 1/2")	5/16"	36 lf (10.97 m)	44 lbs (19.96 kg)	8	64 lf (19.51 m)	81 lbs (36.74 kg)	20	16 lbs (7.257 kg)
Marquee (4 1/4")	3/8"	n/a	n/a	8	64 lf (19.51 m)	53 lbs (24.04 kg)	20	9 lbs (4.082 kg)
Quarter Round (1/2")*	1/2"	n/a	n/a	20	240 lf (73.15 m)	35 lbs (15.88 kg)	n/a	n/a
Regal (5 1/4")	3/8"	n/a	n/a	3	24 lf (7.315 m)	42 lbs (19.05 kg)	20	21 lbs (9.525 kg)
Simple (4")	1/4"	50 lf (15.24 m)	44 lbs (19.96 kg)	8	64 lf (19.51 m)	57 lbs (25.85 kg)	20	9 lbs (4.082 kg)
Simple (4")	3/8"	n/a	n/a	8	64 lf (19.51 m)	57 lbs (25.85 kg)	20	9 lbs (4.082 kg)
Simple (4 1/4")	1/4"	50 lf (15.24 m)	45 lbs (20.41 kg)	8	64 lf (19.51 m)	61 lbs (27.67 kg)	20	10 lbs (4.536 kg)
Simple (4 1/4")	3/8"	n/a	n/a	8	64 lf (19.51 m)	61 lbs (27.67 kg)	20	10 lbs (4.536 kg)
Simplicity (4")	5/16"	36 lf (10.97 m)	44 lbs (19.96 kg)	6	48 lf (14.63 m)	60 lbs (27.22 kg)	20	16 lbs (7.257 kg)
Simplicity (4 1/2")	5/16"	36 lf (10.97 m)	45 lbs (20.41 kg)	6	48 lf (14.63 m)	63 lbs (28.58 kg)	20	11 lbs (4.99 kg)
Simplicity (6")	5/16"	36 lf (10.97 m)	57 lbs (25.85 kg)	4	32 lf (9.754 m)	54 lbs (24.49 kg)	20	24 lbs (10.89 kg)
Sophisticate (4 1/4")	3/8"	n/a	n/a	8	64 lf (19.51 m)	53 lbs (24.04 kg)	20	9 lbs (4.082 kg)

\* Ships in 12' Lengths

**Edge Effects® Collection**

<b>Style</b>	<b>Corner Guard*, Double Etched*, Effectual® Chair Rail, Etched*, Simple</b>	<b>Elegance</b>
<b>Construction</b>	Co-extruded Thermoplastic Rubber, Type TP	Co-extruded Thermoplastic Rubber, Type TP
<b>Classification</b>	ASTM F1861 Type TP, Group 1	ASTM F1861 Type TP, Group 1
<b>Finish</b>	Matte	Matte
<b>Total Thickness</b>	1/4" (6.35 mm)	3/16" (4.76 mm)
<b>Profile</b>	Smooth	Smooth
<b>Profile Height</b>	Corner Guard - 1" Double Etched, Etched, Simple - 4" or 4 1/4" Effectual® Chair Rail - 4" Etched - 6"	6"
<b>Colors</b>	40 (36 are Accord)	40 (36 are Accord)
<b>Packaging</b>	See Packaging Chart, p.4	See Packaging Chart, p.4
<b>Adhesive</b>	MR101 Acrylic	MR101 Acrylic
<b>Testing</b>		
<b>HUD/FHA</b>	Meets / Exceeds	
<b>ADAG (American Disability Act Guidelines)</b>	Passes	
<b>Flexibility (ASTM F137)</b>	Passes - 1/4" Mandrel - No Crack/Break	
<b>Flooring Radiant Panel (ASTM E648)</b>	Passes - Class 1; $\geq 0.45$ watts/cm <sup>2</sup>	
<b>Smoke Density (ASTM E662)</b>	Passes - < 450	
<b>Chemical Resistance (ASTM F925)</b>	Passes - No More Than Slight Change	
<b>Resistance to Heat (ASTM F1514)</b>	Passes - < 8 Delta E Color Change	
<b>Resistance to Mold/Mildew (ASTM G21/E2180)</b>	Passes - No More Than Slight Change	
<b>Environmental Data</b>		
<b>Indoor Air Quality</b>	FloorScore Certified; CDPH v1.1-2010	
<b>LEED Scoreboard</b>	May contribute to LEED credits: LEED 2009: MRc5 Regional Materials; IEQ4.1 Low Emitting Adhesives; IEQ4.3 Low Emitting Materials - Flooring LEED v4: IEQc2 - Low Emitting Materials	
<b>mindful MATERIALS Manufacturing</b>	Visit mM Origin website, <a href="http://mindfulmaterials.origin.build">mindfulmaterials.origin.build</a> for current transparency information USA	
<b>Warranty</b>		
Limited 5 Year Commercial Warranty		

**Edge Effects<sup>®</sup> Collection**

<b>Style</b>	<b>Cetera<sup>®</sup>*, Flair*, Lunar, Simplicity*</b>	<b>Cache<sup>®</sup>*, Etched, Iconic<sup>®</sup>*, Marquee<sup>®</sup>*, Regal*, Simple, Sophisticate<sup>®</sup>*</b>
Construction	Co-extruded Thermoplastic Rubber, Type TP	Co-extruded Thermoplastic Rubber, Type TP
Classification	ASTM F1861 Type TP, Group 1	ASTM F1861 Type TP, Group 1
Finish	Matte	Matte
Total Thickness	5/16" (7.94 mm)	3/8" (9.52 mm)
Profile	Smooth	Smooth
Profile Height	Flair - 3" Cetera <sup>®</sup> , Lunar, Simplicity - 4" or 4 1/2" Simplicity - 6"	Cache <sup>®</sup> - 3" Illusion <sup>®</sup> - 3 1/4" Etched, Simple - 4" or 4 1/4" Cache <sup>®</sup> , Iconic <sup>®</sup> , Marquee <sup>®</sup> , Sophisticate <sup>®</sup> - 4 1/4" Regal - 5 1/4"
Colors	40 (36 are Accord)	40 (36 are Accord)
Packaging	See Packaging Chart, p.4	See Packaging Chart, p.4
Adhesive	MR101 Acrylic	MR101 Acrylic
<b>Testing</b>		
HUD/FHA	Meets / Exceeds	
ADAG (American Disability Act Guidelines)	Passes	
Flexibility (ASTM F137)	Passes - 1/4" Mandrel - No Crack/Break	
Flooring Radiant Panel (ASTM E648)	Passes - Class 1; $\geq 0.45$ watts/cm <sup>2</sup>	
Smoke Density (ASTM E662)	Passes - < 450	
Chemical Resistance (ASTM F925)	Passes - No More Than Slight Change	
Resistance to Heat (ASTM F1514)	Passes - < 8 Delta E Color Change	
Resistance to Mold/Mildew (ASTM G21/E2180)	Passes - No More Than Slight Change	
<b>Environmental Data</b>		
Indoor Air Quality	FloorScore Certified; CDPH v1.1-2010	
LEED Scoreboard	May contribute to LEED credits: LEED 2009: MRc5 Regional Materials; IEQ4.1 Low Emitting Adhesives; IEQ4.3 Low Emitting Materials - Flooring LEED v4: IEQc2 - Low Emitting Materials	
mindful MATERIALS Manufacturing	Visit mM Origin website, <a href="http://mindfulmaterials.origin.build">mindfulmaterials.origin.build</a> for current transparency information USA	
<b>Warranty</b>		
	Limited 5 Year Commercial Warranty	

**Edge Effects® Collection**

<b>Style</b>	<b>Quarter Round</b>	<b>*Pre-mitered Inside and Outside corners also available</b>
Construction	Co-extruded Thermoplastic Rubber, Type TP	Co-extruded Thermoplastic Rubber, Type TP
Classification	ASTM F1861 Type TP, Group 1	ASTM F1861 Type TP, Group 1
Finish	Matte	Matte
Total Thickness	1/2" (12.7 mm)	3/16" (4.76 mm)
Profile	Smooth	Smooth
Colors	40 (36 are Accord)	40 (36 are Accord)
Packaging	See Packaging Chart, p.4	See Packaging Chart, p.4
Adhesive	MR101 Acrylic	MR101 Acrylic
<b>Testing</b>		
HUD/FHA	Meets / Exceeds	
ADAG (American Disability Act Guidelines)	Passes	
Flexibility (ASTM F137)	Passes - 1/4" Mandrel - No Crack/Break	
Flooring Radiant Panel (ASTM E648)	Passes - Class 1; $\geq 0.45$ watts/cm <sup>2</sup>	
Smoke Density (ASTM E662)	Passes - < 450	
Chemical Resistance (ASTM F925)	Passes - No More Than Slight Change	
Resistance to Heat (ASTM F1514)	Passes - < 8 Delta E Color Change	
Resistance to Mold/Mildew (ASTM G21/E2180)	Passes - No More Than Slight Change	
<b>Environmental Data</b>		
Indoor Air Quality	FloorScore Certified; CDPH v1.1-2010	
LEED Scoreboard	May contribute to LEED credits: LEED 2009: MRc5 Regional Materials; IEQ4.1 Low Emitting Adhesives; IEQ4.3 Low Emitting Materials - Flooring	
mindful MATERIALS	LEED v4: IEQc2 - Low Emitting Materials	
Manufacturing	Visit mM Origin website, <a href="http://mindfulmaterials.origin.build">mindfulmaterials.origin.build</a> for current transparency information USA	
<b>Warranty</b>		
	Limited 5 Year Commercial Warranty	