FLOS



Arrangements Broken Line

by Michael Anastassiades , 2018

Diffuse light suspended lighting device. Body in extruded, curved NC-machined and black powder-coated aluminium, diffuser in platinum optical silicone.

Each component can be connected to the power pack by means of an electrical and mechanical connection system designed for customisable product set-up.

Roses available with two powers: lamp with power under 70W and lamp with power under 190W. Class III roses also available for installations with remote power supply: "surface" version for installations on cement, "recessed" version for plasterboard ceilings.


The electronics integrated in the rose enables use of dimming systems: push, 1-10, potentiometer, DALI. In the absence of these systems, the light flow can be set with the push system included in the rose.

Cable length 2.5m

Mounting	Pendant
Environment	Indoor
Finish	Black
Weight	0.65 Kg
Light sources available	1 x Flex strip led 24W 2700K CRI90 2400lm
Emergency	Without
Energency	Without
Voltage	48V
Power	24W
Battery	No
Supply included	No
Cord Length	2500 mm
cord Eengin	2300 mm
Materials	Aluminum
Colors	F0405030 - Black










Arrangements Broken Line by Michael Anastassiades , 2018







F0415030 Big Rose-MAX190W F0416030 Small Rose-MAX70 F0418030 Recessed Rose-MAX190W