BALANCE

Design by Jordi Vilardell.



Reference

5189.

Application

Floor Lamps

Description

Floor light which also acts as a ceiling light. Designed by Jordi Vilardell. Thanks to a small pull chord located at the bottom of the aluminium-weft shade, which also serves as a switch, the shade can be moved to the right or left and up and down while remaining parallel to the floor at all times. It has a dimmer switch in the cable. Available in chrome and matt nickel.

Diffuser

Aluminium-weft diffuser

Finish








Chrome Matt graphite Matt nickel lacquer

Sketch



Electrical characteristics

3 x E27 230V 70W Eco (C)

Total 210.0 W





Physical characteristics

3 Box / 2.44 x 0.18 x 0.19 m. / Vol. 0.3475 $\ensuremath{\text{m}}^{3}$ / Gross weight 51.8 kg. / Net weight 46.6 kg.

Installation and assembly

Please, see the installation manual

Light distribution

General lighting

Lamp for general lighting that equally distributes the light in all directions.


Photometric data

Efficiency: 43.70% Isolux : Floor Coordinate system : CG Light position :

X=0.00m Y=0.00m Z=3.00m Total flux : 1920.00 lm

Maximum value : 88.28 cd/klm Light position: C=0.00 G=0.00

Symmetry on the planes : Double symmetrical



Certificates







