

Cup

design Roberto Pamio



Features



- Ceiling-mounted, pendant and recessed installation.
- Die-cast aluminium body; thick, transparent pressed glass with an internal satin finish.
- High level of light output.



Applications



ceiling-mounted



semi-recessed



pendant

Cup



01
WHITE



15
GREY



65
NITRIC


- **LED Single Chip**
- Colour stability **Mac Adam <3**
- Life 50000 h **L80**
- Color temperature:
Neutral white **4000K**
Warm white **3000K**

lumen lm	LED	QR CBC 51	
800	12W	50W	76%


(3000K) LED energy saving compared with conventional lamps




light source	W	lm	code colour
LED Ceiling-mounted			
Warm white	12W	800	MQ97 01-15




light source	W	lm	code colour
LED Ceiling-mounted			
Warm white	12W	800	MQ98 01-15




light source	W	lm	code colour
LED Recessed			
Warm white	12W	800	MQ99 65
Class of Insulation II			



light source	W	lm	code colour
LED Recessed			
Warm white	12W	800	MR00 65
Class of Insulation II			



light source	W	lm	code colour
LED Pendant			
Warm white	12W	800	MQ95 01-15
Complete with suspension cables and power cable			



light source	W	lm	code colour
LED Pendant			
Warm white	12W	800	MQ96 01-15
Complete with suspension cables and power cable			