

Reference

4125.

**Application** 

Outdoor lamps

Installation type

Surface

Description

Empty is an outdoor lamp that boasts different functions, where matter and light are integrated in a single body. Empty is a sculpture by day and will surprise you with the light it gives off at night. Designed by Xuclà. Available in two finishes: concrete polymer grey and white.

Diffuser

Acrylic diffuser


Finish





Grey polymer White polymer concrete concrete

Sketch



**Electrical characteristics** 

2 x LED STRIP 24V 8,6W

Total 17.2 W





**Physical characteristics** 

1 Box / 0.56 x 0.56 x 0.56 m. / Vol. 0.1760 m<sup>3</sup> / Gross weight 40.0 kg. / Net weight 36.0 kg.

Installation and assembly

Please see the installation manual

**Light distribution** 

# **Ground lighting**


Reduced-height outdoor lamp to shade light on the ground.



Photometric data

Efficiency: 53.22% Isolux: Isolux (Floor) Coordinate system : CG Light position: Total flux : 1247.24 lm X=0.00m Y=0.00m Z=0.45m

Maximum value : 245.05 cd/klm Light position: C=225.00 G=10.00 Double symmetrical: 2













Reference

4130.

**Application** 

Outdoor lamps

Installation type

Surface

Description

Empty is an outdoor lamp that boasts different functions, where matter and light are integrated in a single body. Empty is a sculpture by day and will surprise you with the light it gives off at night. Designed by Xuclà. Available in two finishes: concrete polymer grey and white.

Diffuser

Acrylic diffuser


Finish





Grey polymer White polymer concrete concrete

Sketch



**Electrical characteristics** 

2 x LED STRIP 24V 8,6W

Total 17.2 W





**Physical characteristics** 

1 Box / 0.56 x 0.56 x 0.81 m. / Vol. 0.2540 m<sup>3</sup> / Gross weight 54.7 kg. / Net weight 49.7 kg.

Installation and assembly

Please see the installation manual

**Light distribution** 

# **Ground lighting**


Reduced-height outdoor lamp to shade light on the ground.



Photometric data

Efficiency: 53.22% Coordinate system : CG Total flux : 1247.24 lm

Maximum value : 245.05 cd/klm Light position: C=225.00 G=10.00



Isolux: Isolux (Floor)

X=0.00m Y=0.00m Z=0.70m

Light position:













Reference

4135.

**Application** 

Outdoor lamps

Installation type

Surface

Description

Empty is an outdoor lamp that boasts different functions, where matter and light are integrated in a single body. Empty is a sculpture by day and will surprise you with the light it gives off at night. Designed by Xuclà. Available in two finishes: concrete polymer grey and white.

Diffuser

Acrylic diffuser

Finish





Grey polymer White polymer concrete concrete

Sketch



**Electrical characteristics** 

2 x LED STRIP 24V 4,3W

Total 8.6 W





**Physical characteristics** 

1 Box / 0.36 x 0.36 x 0.36 m. / Vol. 0.0460 m<sup>3</sup> / Gross weight 12.2 kg. / Net weight 10.4 kg.

Installation and assembly

Please see the installation manual

**Light distribution** 

# **Ground lighting**


Reduced-height outdoor lamp to shade light on the ground.



Photometric data

Efficiency: 53.60% Isolux: Isolux (Floor) Coordinate system : CG Light position: Total flux: 566.80 lm X=0.00m Y=0.00m Z=0.25m

Maximum value : 257.32 cd/klm Light position: C=195.00 G=5.00















Reference

4136.

**Application** 

Outdoor lamps

Installation type

Surface

Description

Empty is an outdoor lamp that boasts different functions, where matter and light are integrated in a single body. Empty is a sculpture by day and will surprise you with the light it gives off at night. Designed by Xuclà. Available in two finishes: concrete polymer grey and white.

Diffuser

Acrylic diffuser


Finish





Grey polymer White polymer concrete concrete

Sketch



**Electrical characteristics** 

2 x LED STRIP 24V 4,3W

Total 8.6 W





**Physical characteristics** 

1 Box / 0.36 x 0.36 x 0.65 m. / Vol. 0.0840 m<sup>3</sup> / Gross weight 22.0 kg. / Net weight 19.0 kg.

Installation and assembly

Please see the installation manual

**Light distribution** 

# **Ground lighting**

Reduced-height outdoor lamp to shade light on the ground.



Photometric data

Efficiency: 53.60% Isolux: Isolux (Floor) Coordinate system : CG Light position: Total flux: 566.80 lm X=0.00m Y=0.00m Z=0.55m

Maximum value: 257.32 cd/klm Light position: C=195.00 G=5.00

