## Glo-Ball Ceiling/Wall Zero

by Jasper Morrison , 2009

Wall or ceiling lamp providing diffused light. Diffuser consisting of an externally acidetched, hand blown, flashed opaline glass and a die-cast aluminum threaded ring nut with alodine plating finish. 30% fiberglass reinforced injection molded polyamide base. Gray painted, die-cast aluminum diffuser support.

> Ceiling/wall Indoor

Finish White Weight 1 Kg Light sources available 1 x LED 8W E14 800lm 3000K cod. RF26565 [e] DIMMER 1 x LED 8W E14 700lm 2700K cod. RF26767 [e] DIMMER 1 x LED 10W E14 800lm 2700K cod. RF26261 [e] DIMMER 1 x LED 10W E14 900Im 3000K cod. RF26260 [e] DIMMER Without Emergency Voltage 220-250V MAX 60W Power No Battery Supply included Yes

Mounting

Environment

Materials

Colors


Certificate


CE	<b>K</b> 03 <sup>7</sup>	F/	IP 40	

F3335009 - White

Glass








## **Glo-Ball Ceiling 1**


by Jasper Morrison , 1999



Ceiling mounted lamp providing diffused light. Diffuser consisting of an externally acidetched, hand blown, flashed opaline glass and of a die-cast aluminum threaded ring nut with alodine plating finish. 30% fiberglass reinforced injection-molded polyamide ceiling fitting; gray painted die-cast aluminum diffuser support.







Mounting	Ceiling
Environment	Indoor
Finish	White
Weight	2.5 Kg
Light sources available	1 x MAX 150W E27 HSGS 2870lm 2900K [e] cod. RF20358 DIMMER 1 x LED 13W E27 1400lm 3000K [e] cod. RF25535 DIMMER 1 x LED 13W E27 1400lm 2700K [e] cod. RF26065 DIMMER 1 x LED 17W E27 2000lm 2700K [e] cod. RF26259 DIMMER 1 x LED 17W E27 2000lm 3000K [e] cod. RF26258 DIMMER
Emergency	Without
Voltage	220-250V
Power	MAX 150W
Battery	No
Supply included	Yes
Materials	Glass
Colors	F3023000 - White
Certificate	

## Glo-Ball Ceiling 2

by Jasper Morrison , 1999


Ceiling mounted lamp providing diffused light. Diffuser consisting of an externally acidetched, hand blown, flashed opaline glass and of a die-cast aluminum threaded ring nut with alodine plating finish. 30% fiberglass reinforced injection-molded polyamide ceiling fitting; gray painted die-cast aluminum diffuser support.


Mounting	Ceiling
Environment	Indoor
Finish	White
Weight	5.1 Kg
Light sources available	1 x LED 13W E27 1400lm 3000K [e] cod. RF25535 DIMMER 1 x LED 17W E27 1900lm 2700K [e] cod. RF26259 DIMMER 1 x LED 17W E27 2000lm 3000K [e] cod. RF26258 DIMMER 1 x LED 13W E27 1400lm 2700K [e] cod. RF26065 DIMMER
Emergency	Without
Voltage	220-250V
Power	MAX 250W
Battery	No
Supply included	Yes
Materials	Glass

Colors F3028000 - White

€ ∰ □

Certificate







ø145 mm

ø 450 mm

360 mm

