

Ceiling-mounted

∅ 51



∅ 81



∅ 132



Wall-mounted

∅ 51



∅ 81



∅ 132



Lighting effect



Down light
L



Down light
L



Up / Down light
L/F
W/F/WF
L/L

∅ 155



∅ 192



∅ 155



∅ 192



Floodlights

The complete range and technical and lighting features are presented on page 630



∅ 51



∅ 81



∅ 132



∅ 155



∅ 192





∅ 51



∅ 81



Explore and interact with products in 3D.
thelightexperience.iguzzini.com



- Floodlight luminaire intended for use with LED light sources.
- Wall and ceiling installation.
- Optical compartment, upper cap for ceiling installation and side base strip for wall installation in die-cast aluminium; transparent tempered sodium-calcium sealing glass, 4 mm thick, applied with silicon on the optical assembly.

- All products are complete with thermoplastic high reflection lenses or luminous flux recovery units.
- Body versions ∅ 81 complete with electronic power supply (Vin 100 ÷ 240Vsc 50 / 60Hz); body ∅ 81 with electronic power supply to be ordered separately (500/700mA, versions CLIII) except for wall-mounted up/down light.

- Luminaire ready for pass-through wiring.
- All external screws used are in A2 stainless steel.



Compact dimensions