

# Trick

## Washer effect

design Dean Skira



ø45



ø90



Explore and interact with products in 3D.  
[thelightexperience.iguzzini.com](http://thelightexperience.iguzzini.com)

LMS




IP66

IK07



- Luminaire intended for warm white colour temperature. LED light sources.
- Recessed luminaire (ø 45 mm) and applique (ø 90 mm) versions.
- Applique versions have a screen and base support strip. PMMA screen, die-cast aluminium supporting base, stainless steel plate for fixing to wall, supplied with L=400 mm cable (except versions with power supply).
- Versions with and without built-in power supply unit.

- Recessed luminaires comprise a die-cast aluminium screen and body and stainless steel springs.
- Wall-washer optic.
- Compatible with light management systems.
- Contact temperature <50 °C.
- Compact dimensions.
- All external screws used are in A2 stainless steel.




Adjustable base strip for oblique surfaces



Compact dimensions

### Lighting effects

The Washer optic gives a wall washer effect using a miniaturized luminaire camouflaged in the area where it is installed.






01  
WHITE

15  
GREY




source		system		code	colour
W	lm	W	lm		
<b>360° Blade Effect - Surface-mounted</b>					
<b>LED</b>					
3000K - CRI 80					
5,7W	720	6W	108	<b>BU27</b>	01-15
RGB - DMX-RDM					
6W	160	6W	35	<b>BW06</b>	01-15
Power supply 350 mA to be ordered separately.					



source		system		code	colour
W	lm	W	lm		
<b>180° Blade Effect - Surface-mounted</b>					
<b>LED</b>					
3000K - CRI 80					
2,9W	350	3W	88	<b>BU16</b>	01-15
Power supply 350 mA to be ordered separately.					



source		system		code	colour
W	lm	W	lm		
<b>180° Blade Effect - Surface-mounted</b>					
<b>LED</b>					
3000K - CRI 80					
2,9W	350	3,9W	88	<b>BU22</b>	01-15
Complete with power supply Class of Insulation II					



**Mounting accessories**

	code	colour
Adjustable base strip	<b>MZ53</b>	13
For BU16-BU27-BU28-BW06		

**Interfaces & remote units**

	code	colour
Driver for Trick mounting	<b>X295</b>	00

	code	colour
Driver for Trick with IP67 box	<b>MZ72</b>	00

	code	colour
LMS Quick DMX	<b>MZ73</b>	01-04
For BW06		

	code	colour
LMS Quick PRO-DMX	<b>X294</b>	01-04
For BW06		

**Control gear**

	code	colour
IP67 box for power supply		
dim. 140x230x95h (6PG)	<b>9582</b>	00

	code	colour
dim. 280x190x130h (10PG)	<b>BZ33</b>	00
For BU16-BU27-BU28-BW06		

	code	colour
Sealed connector kit IP68	<b>9581</b>	04

**Power supply**

	code	colour
Constant current power supply unit non dimmable IP20 7W		
VIN = 100-240VAC 50/60Hz Iout = 350mA/500mA dimensions: 42x40x22	<b>9905</b>	00
For BU16-BU27-BU28		

	code	colour
Constant current power supply unit non dimmable IP20 17W		
VIN = 220-240VAC 50/60Hz Iout = 350mA dimensions: 122x38x28	<b>9907</b>	00

	code	colour
Constant current power supply unit non dimmable IP20 20W		
VIN = 220-240VAC 50/60Hz Iout = 350mA/500mA/700mA dimensions: 110x52x22	<b>X020</b>	00
For BU16-BU27-BU28		

	code	colour
Electronic power supply for Trick RGB	<b>MZ74</b>	00

**Power supply**

	code	colour
Constant current power supply unit DALI IP20 20W		
VIN = 110-127/220-240VAC 50/60Hz Iout = 350/500/700mA dimensions: 110x52x22	<b>X090</b>	00
For BU16-BU27-BU28		

	code	colour
Constant current power supply unit non dimmable track DIN 120W		
VIN = 220-240VAC 50/60Hz Vout = 48V-55V IMAX = 2,5A dimensions: 40x114x125	<b>BZ14</b>	00

	code	colour
Constant current power supply unit non dimmable track DIN 240W		
VIN = 220-240VAC 50/60Hz Vout = 48V-55V IMAX = 5A dimensions: 63x114x125	<b>BZ15</b>	00

	code	colour
Constant current power supply unit non dimmable track DIN 480W		
VIN = 220-240VAC 50/60Hz Vout = 48V-55V IMAX = 10A dimensions: 85x128x125	<b>BZ16</b>	00