WIREFLOW

Design by Arik Levy.

Reference

0301.

Application Hanging lamps

Installation type

Surface

Description

Wireflow designed by Arik Levy. A hanging lamp which reviews and updates the chandelier look through an exercise of simplification that explores its essence and enhances its outline with great delicacy and at the same time a strong formal presence. Its appearance, as a structure of fine cables finished with eight 3.7W LED terminals, discretely connects with classic chandelier models, taking this type of lamp to a new, groundbreaking and futuristic dimension. Employing CREA product configurator software, the design can be modified to adapt to your specific project requirements.

Diffuser


Pressed-glass diffuser

Finish



0301-04 Black lacquer

Sketch



Electrical characteristics 8 x LED 3,7W 350mA

Õ

Total 29.6 W





LIGHT IS CREATION

Physical characteristics

2 Box / 0.09 x 1.16 x 1.13 m. / Vol. 0.2100 m³ / Gross weight 17.8 kg. / Net weight 8.8 kg.

Installation and assembly Please see the installation manual

Light distribution

General lighting


Lamp for general lighting that equally distributes the light in all directions.



Photometric data

Efficiency : 54.92% Coordinate system : CG Total flux : 3408.00 lm Maximum value : 73.75 cd/klm Light position : C=15.00 G=55.00 Double symmetrical : 3

Isolux : Isolux (Floor) Light position : X=0.00m Y=0.00m Z=3.00m



Certificates

