


IP20 🔲 🔣 🕫 CE

TECHNICAL DRAWINGS



DESIGN BY

Neri&Hu

DESCRIPTION

The activity of Neri&Hu is founded on constant research and the desire to work on the dynamic interaction of experience, detail, material, shape, and light, rather than adapt to stereotyped formulas. In a blend of tradition and innovation, Yanzi is a lightweight composition of graphic signs. Balanced structures, such as branches or perches, support multiple stylized figures to provide a variety of versions and qualities of light. They are iconic swallows with a brushed brass body, with their head like a white glass sphere enclosing light, either flying free or contained in glass cages. There is unique sensibility in matching warm and cold, essential yet refined materials. Yanzi is an open system, ideal for creating lightweight compositions and light landscapes that animate any space with an elegant poetic attitude.

FEATURES

Watt:7.8WCRI:90Delivered lumens output (Im):841ImEfficacy:107Im/WType:0Service Life:50000-L70Class:ADelivered lumens output (Im):1414ImVoltage:20WDelivered lumens output (Im):1414ImVoltage:220-240VCCT:3000KEfficiency:84%Efficacy:71Im/WCRI:90				
white, black Table, Floor, SuspensionSeries: Emission:Design DiffusedEnvironment:IndoorDiffusedDIMENSIONS	Article Code:	1102010A	Material:	Brushed brass,
Installation:Table, Floor, SuspensionEmission:DiffusedEnvironment:IndoorDiffusedDiffusedDIMENSIONScm 40cm 75.4Height: cm 192cm 192Base Diameter:cm 40cm 40cm 40INCLUDED SOURCESColor temperature (K): color Tolerance:3000KNumber:2Color Tolerance: 90MacAdam 2SDCIWatt:7.8WCRI: Service Life:90Delivered lumens output (Im):841Im Type: Class:Efficacy: 3000K107Im/WLUMINAIRE20WDelivered lumens output (Im):1414Im Service Life:3000KWatt:20WDelivered lumens output (Im):1414Im CCT:3000KKutt:20WDelivered lumens output (Im):1414Im CCT:3000KWatt:220-240VCCT: CCT:3000KKutt:220-240VCCT: CCT:3000KKutt:200CCT: CCT:3000KKutt:200CCT: CT:3000KKutt:200CCT: CT:3000KKutt:200CCT: CT:3000KKutt:200CCT: CT:3000KKutt:200CCT: CT:3000KKutt:200CCT: CT:3000KKutt:200CCT: CT:3000KKutt:200CCT: CT:3000KKutt:200CCT: CT:3000KKutt:CCT: CT:3000KKutt:CCT: CT:3000KKu	Colour:	Brushed brass,		blown glass
Suspension SuspensionEndertain SuspensionEnvironment:IndoorDIMENSIONSLength:cm 40Width:cm 75.4Height:cm 192Base Diameter:cm 40INCLUDED SOURCESColor temperature (K):3000KCategory:LEDColor Tolerance:MacAdam 2SDCINumber:2Color Tolerance:MacAdam 2SDCIWatt:7.8WCRI:90Delivered lumens output (Im):8411mEfficacy:1071m/WType:0Service Life:50000-L70Class:AEfficacy:3000KEUMINAIRE20WDelivered lumens output (Im):14141mVoltage:209Delivered lumens output (Im):14141mCCT:3000KEfficiency:84%Efficiency:84%Efficiency:84%Efficiency:90		white, black	Series:	Design
Environment:IndoorDIMENSIONSLength:cm 40Width:cm 75.4Height:cm 192Base Diameter:cm 40INCLUDED SOURCESCategory:LEDQColor temperature (K):3000KNumber:2Color Tolerance:MacAdam 2SDCIWatt:7.8WCRI:90Delivered lumens output (Im):841ImEfficacy:107Im/WType:0Service Life:50000-L70Class:AEfficacy:3000KLUMINAIRE20WDelivered lumens output (Im):1414ImVoltage:202-240VCCT:3000KEfficiency:84%Efficiency:84%Efficiency:84%Efficacy:71Im/WOCCT:3000KEfficiency:84%Efficacy:71Im/WOCCT:3000KEfficiency:84%Ef	Installation:	Table, Floor,	Emission:	Diffused
DIMENSIONS Length: cm 40 Width: cm 75.4 Height: cm 192 Base Diameter: cm 40 INCLUDED SOURCES Color temperature (K): 3000K Number: 2 Color Tolerance: MacAdam 2SDCI Watt: 7.8W CRI: 90 Delivered lumens output (Im):841Im Efficacy: 107Im/W Type: 0 Service Life: 50000-L70 Class: A 2000 CCT: 3000K Efficiency: 220-240V CCT: 3000K Efficiency: 84% Efficiency: 84% Efficiency: 84% Efficiency: 84% Efficiency: 84% Efficacy: 711m/W Voltage: Voltage: 90 Voltage: 90		Suspension		
Length:cm 40Width:cm 75.4Height:cm 192Base Diameter:cm 40INCLUDED SOURCESCategory:LEDColor temperature (K):3000KNumber:22Color Tolerance:Watt:7.8W7.8WCRI:90Delivered lumens output (Im):8411mEfficacy:107lm/WType:0Service Life:50000-L70Class:ALUMINAIREWatt:20WVoltage:220-240VCCT:3000KEfficiency:84%Efficacy:71lm/WCRI:90	Environment:	Indoor		
Length:cm 40Width:cm 75.4Height:cm 192Base Diameter:cm 40INCLUDED SOURCESCategory:LEDColor temperature (K):3000KNumber:22Color Tolerance:Watt:7.8W7.8WCRI:90Delivered lumens output (Im):8411mEfficacy:107lm/WType:0Service Life:50000-L70Class:ALUMINAIREWatt:20WVoltage:220-240VCCT:3000KEfficiency:84%Efficacy:71lm/WCRI:90				
Width:cm 75.4Height:cm 192Base Diameter:cm 40INCLUDED SOURCESColor temperature (K):3000KCategory:LEDColor Tolerance:MacAdam 2SDCIWatt:7.8WCRI:90Delivered lumens output (Im):8411mEfficacy:1071m/WType:0Service Life:50000-L70Class:ADelivered lumens output (Im):1414lmVatt:20WDelivered lumens output (Im):1414lmVoltage:20-240VCCT:3000KEfficiency:84%Efficacy:711m/WOCRI:90	DIMENSIONS			
Height: cm 192 Base Diameter: cm 40 INCLUDED SOURCES Color temperature (K): 3000K Number: 2 Color Tolerance: MacAdam 2SDCI Watt: 7.8W CRI: 90 Delivered lumens output (Im):8411m Efficacy: 107lm/W Type: 0 Service Life: 50000-L70 Class: A LUMINAIRE 20W Delivered lumens output (Im):1414lm Voltage: 20-240V CCT: 3000K Efficiency: 84% Efficiency: 84% Efficacy: 71lm/W RI: 90	Length:	cm 40		
Base Diameter:cm 40INCLUDED SOURCESLEDColor temperature (K):3000KNumber:2Color Tolerance:MacAdam 2SDCIWatt:7.8WCRI:90Delivered lumens output (Im):8411mEfficacy:107lm/WType:0Service Life:50000-L70Class:ALUMINAIREWatt:20WDelivered lumens output (Im):1414lmVoltage:20-240VCCT:3000KEfficiency:84%Efficacy:71lm/WCRI:90901000K	Width:	cm 75.4		
INCLUDED SOURCES Category: LED Color temperature (K): 3000K Number: 2 Color Tolerance: MacAdam 2SDCI Watt: 7.8W CRI: 90 Delivered lumens output (Im):8411m Efficacy: 1071m/W Type: 0 Service Life: 50000-L70 Class: A LUMINAIRE Watt: 20W Delivered lumens output (Im):1414lm Voltage: 220-240V CCT: 3000K Efficiency: 84% Efficacy: 711m/W CRI: 90	Height:	cm 192		
Category:LEDColor temperature (K):3000KNumber:2Color Tolerance:MacAdam 2SDCIWatt:7.8WCRI:90Delivered lumens output (Im):8411mEfficacy:107lm/WType:0Service Life:50000-L70Class:AEfficiency:3000KLUMINAIRE20WDelivered lumens output (Im):1414lmVoltage:220-240VCCT:3000KEfficiency:84%Efficacy:71lm/WCRI:90901000	Base Diameter:	cm 40		
Number:2Color Tolerance:MacAdam 2SDCIWatt:7.8WCRI:90Delivered lumens output (lm):8411mEfficacy:1071m/WType:0Service Life:50000-L70Class:AService Life:1071m/WLUMINAIRE20WDelivered lumens output (lm):1414lm1414lmVoltage:220-240VCCT:3000KEfficiency:84%Efficacy:711m/WCRI:90901414m	INCLUDED SOURCE	S		
Number:2Color Tolerance:MacAdam 2SDCIWatt:7.8WCRI:90Delivered lumens output (lm):8411mEfficacy:1071m/WType:0Service Life:50000-L70Class:AService Life:1071m/WLUMINAIRE20WDelivered lumens output (lm):1414lm1414lmVoltage:220-240VCCT:3000KEfficiency:84%Efficacy:711m/WCRI:90901414m	Category:	LED	Color temperature (K):	3000K
Delivered lumens output (Im):841Im Efficacy: 107Im/W Type: 0 Service Life: 50000-L70 Class: A Delivered lumens output (Im):1414Im Voltage: 220-240V CCT: 3000K Efficiency: 84% Efficacy: 71Im/W CRI: 90	Number:	2		MacAdam 2SDCM
Type:0Service Life:50000-L70Class:ALUMINAIREWatt:20WDelivered lumens output (lm):1414lmVoltage:220-240VCCT:3000KEfficiency:84%Efficacy:71lm/WCRI:90	Watt:	7.8W	CRI:	90
Class: A LUMINAIRE Watt: 20W Delivered lumens output (lm):1414lm Voltage: 220-240V CCT: 3000K Efficiency: 84% Efficacy: 71lm/W CRI: 90	Delivered lumens output (lm):841lm		Efficacy:	107lm/W
LUMINAIRE Watt: 20W Delivered lumens output (lm):1414lm Voltage: 220-240V CCT: 3000K Efficiency: 84% Efficacy: 71lm/W CRI: 90	Туре:	0	Service Life:	50000-L70
Watt: 20W Delivered lumens output (lm):1414lm Voltage: 220-240V CCT: 3000K Efficiency: 84% Efficacy: 71lm/W CRI: 90	Class:	А		
Voltage: 220-240V CCT: 3000K Efficiency: 84% Efficacy: 71lm/W CRI: 90	LUMINAIRE			
Efficiency: 84% Efficacy: 71lm/W CRI: 90	Watt:	20W	Delivered lumens output (lm):1414lm	
Efficacy: 71lm/W CRI: 90	Voltage:	220-240V	CCT:	3000K
Efficacy: 71lm/W CRI: 90	-		Efficiency:	84%
CRI: 90			-	71lm/W
			CRI:	90
Dimmer Typology: I ouch Dimmer			Dimmer Typology:	Touch Dimmer