

# 12

12 SPECIFICATION SHEET / 1 OF 2 / 080921



12-O-W

## SURFACE DOUBLE OUTLET



12-O-B/W

Simplified, surface mounted power outlets with a slim 2.9mm profile.



### SPECIFICATIONS

DIMENSIONS	H51 X W136 X D24 mm
MATERIAL	POLYCARBONATE
REGION	AU/NZ
APPLICATION	INTERIOR
WEIGHT	66.35 g
CAPSULE CUTOUT	H35 X W120 mm
MINIMUM MOUNTING DEPTH	20 mm
IP	IP20
ELECTRICAL SWITCHING	10A AT 250V AC 50HZ
SAFETY	AUTO-SWITCHING MECHANISM SAFETY SHUTTERS INCLUDED
STANDARDS	AS/NZS 3112, 3100, 60950
COMPLIANCE NUMBER	SGS-210439-EA
PRODUCT CERTIFICATION	RCM
PATENT	PATENT PENDING

### FINISHES

	
MATTE WHITE	MATTE BLACK
[W]	[B]

### COMPATIBLE ACCESSORIES INDEX

	PRODUCT	SKU
	SURFACE RENDER BRACKET	12-RB
	SURFACE Z CLIP	12-ZC

SPECIFICATIONS ARE SUBJECT TO CHANGE WITHOUT PRIOR NOTICE

# 12



12-O-B

## ORDER GUIDE

	SERIES		TYPE		COLOUR
<i>E.G.</i>	12		OUTLET		BLACK
<i>CODE</i>	12	-	O	-	B

## PACKAGING SPECIFICATIONS

INDIVIDUAL PACK PCS	1
GROUP PACK PCS	5
GROUP PACK SIZE	D137 X W150 X H53 mm
BULK PACK PCS	50
BULK PACK SIZE	D280 X W315 X H150 mm

## CLEANING & MAINTENANCE

To clean, simply wipe with a soft damp cloth or detergent-impregnated wipes. Under no circumstance should you spray cleaning solution directly onto the product or use abrasive or solvent type cleaners. If you notice deterioration or damage to this product over time, contact a licensed electrician to repair and/ or replace the damaged product immediately

