

# 13

13 SPECIFICATION SHEET / 1 OF 2 / 011221



13-O-W



13-O-USB-W



13-O-USB-B

RANGE INDEX

## FLUSH DOUBLE OUTLET

13-O-B/W

Recessed, trimless, and completely flush power outlets.

### SPECIFICATIONS




DIMENSIONS	H46 X W132 X D33 mm
MATERIAL	POLYCARBONATE
REGION	AU/NZ
APPLICATION	INTERIOR
WEIGHT	99.35 g
CAPSULE CUTOUT	SEE MOUNTING ACCESSORY
IP	IP20
MINIMUM MOUNTING DEPTH	SEE MOUNTING ACCESSORY
ELECTRICAL	10A AT 250V AC 50HZ
SWITCHING	AUTO-SWITCHING MECHANISM
SAFETY	SAFETY SHUTTERS INCLUDED
STANDARDS	AS/NZS 3112, 3100, 60950
COMPLIANCE NUMBER	SGS-170519-EA
PRODUCT CERTIFICATION	RCM
PATENT	2018203470

### FINISHES



MATTE WHITE [W]  
MATTE BLACK [B]

### COMPATIBLE ACCESSORIES INDEX

	PRODUCT	SKU
	FLUSH FIXED MOUNTING	13-FMA
	FLUSH ADJUSTABLE MOUNTING	13-AMA-B/W
	FLUSH FIRE RATED ENCLOSURE	13-FRE*

NB. OUTLET FINISH TO MATCH 13-AMA COLOUR.

\*13-FRE MUST BE INSTALLED IN CONJUNCTION WITH 13-FMA/AMA.

SPECIFICATIONS ARE SUBJECT TO CHANGE WITHOUT PRIOR NOTICE

# 13



13-O-B

## ORDER GUIDE

	SERIES	TYPE	OPTIONS	COLOUR
E.G.	13	OUTLET	/	BLACK
CODE	13	- O -	/	B

## PACKAGING SPECIFICATIONS

INDIVIDUAL PACK SIZE	D47 X W145 X H32 mm
GROUP PACK PCS	4
GROUP PACK SIZE	D137 X W150 X H53 mm
BULK PACK PCS	40
BULK PACK SIZE	D280 X W315 X H150 mm

## CLEANING & MAINTENANCE

To clean, simply wipe with a soft damp cloth or detergent-impregnated wipes. Under no circumstance should you spray cleaning solution directly onto the product or use abrasive or solvent type cleaners. If you notice deterioration or damage to this product over time, contact a licensed electrician to repair and/ or replace the damaged product immediately

