




Access Control Cable

**18AWG 4C + 22AWG 2C + 22AWG 4C + 22AWG 3PAIR SHLD
CMP(Plenum Rated)**

Cable Structure



Electrical Performance

Conductor DC Resistance at 20°C	
22AWG	≤55.4Ω/km
18AWG	≤21.9Ω/km

Applications

- Card Readers
- Locking Power
- Door Contacts
- Retina Scanners

Temperature Range

Temp Rating:	75°C
Operating Temp Range:	-20°C To +75°C

Color Code Chart

Cond	Color
1	White/Purple Stripe
2	White/Yellow Stripe
3	White/Green Stripe
4	White/Red Stripe

Standard & Application

c(ETL)	Indoor Communication
CE	Remote Control
RoHS	Signalling

Construction

- Conductor:Bare Copper
- Insulation: Low Smoke, color-coded PVC
- Rid cord: A nylon rip cord under jacket for ease of jacket stripping
- Shield: Overall polyester backed aluminum foil, with 26AWG tinned copper drain wire
- Jacket: Low Smoke yellow PVC jacket

Specifications

P/N	Overall Nominal O.D.	Comp.No	Comp. Desc.	Cond Colors	Comp.No minial O.D.	Ins. Thicknes s
PCOMBO16C-YE	.430	1	18AWG 4 COND	White	.183	.008
				Red		
				Black		
				Green		
		2	22AWG 3PR	Black/Red	.205	.007
				White/Green		
				Brown/Orange		
		3	22AWG 2 COND	Black	.128	.007
				Red		
		4	22AWG 4 COND	White	.138	.007
				Black		
				Red		
Green						

Packing

1,000' Wooden Reel /pallet



Printing:

PSI DATA ACCESS CONTROL CABLE 18AWG 4C + 22AWG 2C + 22AWG 4C + 22AWG 3PAIR SHLD 75C c(ETL)us TYPE CMP xxxxxxx FT6 "ROHS" DOOR/ZONE A B C D E 0 1 2 3 4 5 6 7 8 9 0000FT/1000FT

Remarks:

The information on this document is, to our knowledge, true and accurate. However, since the particular uses and the actual conditions of use of our products are beyond our control, establishing satisfactory performance of our products for the intended application is the customer's sole responsibility. All uses of PSI products and any written or oral information, suggestions or technical advice from PSI is without warranty, express or implied, and is not an inducement to use any product in conflict with any patent.