

58.4V 22A LiFePO₄ BATTERY CHARGER EX-CHG-48022



PERFORMANCE: High efficiency
Wide input voltage range

FEATURES: Designed for 48V GC2 Series Battery
Active cooling
IP66

Input Parameters	
AC Input Operating Voltage	85 Vac - 120 Vac
AC Input Frequency Range	40 Hz - 70 Hz
Input	3 prong AC plug
Suitable for Batteries	LiFePO ₄ battery
Output Parameters	
Max. Output Voltage	58.4 V
Max. Output Current	22 A @ 120 Vac input
Output	Anderson quick disconnect with 5 ft. DC cable

Mechanical Parameters	
Dimensions	11.1 in x 6.6 in x 3.7 in
	(282 mm x 168 mm x 95 mm)
Weight	8.5 lb (3.9 kg)
Waterproof Rating	IP66
Cooling Mode	Active Fan
Temperature Parameters	
Operating and Storage Temperature	-4 °F to 120 °F (-20 °C to 50 °C)

WARNING: *Do not block Fan.
*Connect DC output before connecting to AC.
*Do not reverse connect DC output.
*Do not short DC output.

DISCLAIMER: While every precaution has been taken to ensure the accuracy of the contents within this document, Expion360, Inc. assumes no responsibility for errors or omissions. Specifications and product functionality may change without notice.