

**Serie | 4, wall-mounted cooker hood,
80 cm, clear glass black printed
DWK87CM60B**



Optional accessories

DSZ5201 : CleanAir active carbon filter spare part
 DWZ0AK0AO : Active carbon filter (spare part)
 DWZ0AK0RO : Recirculation kit regenerative chimless
 DWZ0AK0SO : Recirculation kit regenerative
 DWZ0AK0TO : Recirculation kit for chimless use
 DWZ0AK0UO : Recirculation kit
 DWZ0AX5K0 : Chimney extension 1000 mm
 DWZ0AX5L0 : Chimney extension 1500 mm
 DZZ0XX0P0 : CleanAir act.carbon filter regenerative

**Angled hood: perfect for keeping an eye on
your pots and pans.**

- **Especially silent:** maximum extractor performance with minimal noise
- An impressive extraction rate of 700 m³/h ensures this hood will have your kitchen odour free in no time.
- **TouchSelect control:** quick touch-control selection of desired settings and light.
- **Easy-to-clean interior:** hidden screws and cables along with rounded edges make cleaning easy.
- **Illumination:** The energy-saving lighting provides bright and clear lighting for the hob area.

Technical Data

| | |
|---|--------------------|
| Color chimney : | Stainless steel |
| Typology : | Chimney |
| Approval certificates : | CE, VDE |
| Length electrical supply cord (cm) : | 130 |
| Height of product, without chimney (mm) : | 323 |
| Minimum distance above an electric hob : | 450 |
| Minimum distance above a gas hob : | 600 |
| Net weight (kg) : | 20.873 |
| Type of control : | Electronic |
| Maximum output air extraction (m ³ /h) : | 416 |
| Boost position output recirculating (m ³ /h) : | 557 |
| Maximum output recirculating air (m ³ /h) : | 388 |
| Boost position air extraction (m ³ /h) : | 700 |
| Number of lights : | 2 |
| Noise level (dB(A) re 1 pW) : | 58 |
| Diameter of air outlet (mm) : | 120 / 150 |
| Grease filter material : | Washable aluminium |
| EAN code : | 4242005172733 |
| Connection Rating (W) : | 263 |
| Current (A) : | 10 |
| Voltage (V) : | 220-240 |
| Frequency (Hz) : | 60; 50 |
| Plug type : | GB plug |
| Installation typology : | Wall-mounted |



Serie | 4, wall-mounted cooker hood, 80 cm, clear glass black printed DWK87CM60B

Angled hood: perfect for keeping an eye on your pots and pans.

Key performance features:

- Energy Efficiency Class: B (at a range of energy efficiency classes from A++ to E)*
- Extraction rate according to EN 61591 ø 15 cm: max. Normal use 416 m³/h Intensive 700 m³/h
- Noise max. Normal Level: 58 dB*

Special features

- TouchControl with Electronic display
- 3 power levels & intensive setting
- 2 x 1.5W LED light
- Colour Temperature: 3500 K
- Automatic intensive revert (6mins)
- 2 metal grease filter cassettes
- easy to clean Inner frame
- Designed for wall mounted installation
- Rim ventilation

Design

- Black glass canopy
- angled glass design
- Chimney extractor hood
- TouchControl
- Electronic control

Performance/technical information

- Suitable for ducted or recirculating operation
- For recirculated extraction recirculating kit (accessory) needed
- In recirculation operation chimless use possible
- Easy installation system
- Extraction rate according to EN 61591 ø 15 cm: max. Normal use 416 m³/h Intensive 700 m³/h
- Extraction rate according to EN 61591 max. 416 m³/h
- Noise level according to EN 60704-3 and EN 60704-2-13 at max. normal use exhaust air: 58 dB(A) re 1 pW (45 dB(A) re 20 µPa sound pressure)
- Noise level according to EN 60704-3 and EN 60704-2-13 exhaust air: Max. normal use: 58 dB(A) re 1 pW (45 dB(A) re 20 µPa sound pressure) Intensive: 67 dB(A) re 1 pW (54 dB(A) re 20 µPa sound pressure)
- Noise level according to EN 60704-3 and EN 60704-2-13 at maximum normal setting: extraction rate: 58 dB (A) re 1pW
- Noise max. Normal Level: 58 dB*
-
- Light Intensity: 90 lux
- Colour Temperature: 3500 K
- Electrical cable length 1.3 m
- Diameter pipe ø 150 mm (ø 120 mm enclosed)
- Dimensions exhaust air (HxWxD): 928-1198 x 790 x 499 mm
- Dimensions recirculating (HxWxD): 988-1258 x 790 x 499 mm
- Dimensions recirculating with CleanAir module (HxWxD): 1118 x 790 x 499 mm - mounting with outer chimney 1188-1458 x 790 x 499 mm - mounting with telescopic chimney
- Energy Efficiency Class: B (at a range of energy efficiency classes from A++ to E)*
- Blower Efficiency Class: B*
- Lighting Efficiency Class: B*
- Grease Filtering Efficiency Class: C*
- Average Energy Consumption: 56.6 kWh/year*

Optional accessories

- Recirculating kit

* In accordance with the EU-Regulation No 65/2014