

**Serie | 6, wall-mounted cooker hood,
60 cm, Stainless steel
DWB68JQ50B**



A

Wall mounted chimney hoods add style and sophistication to the kitchen and give you complete freedom in your kitchen planning.

- **EcoSilence Drive:** our highly efficient motor saves on energy, not on performance.
- **PerfectAir sensor:** automatic control of settings for maximum extractor performance with minimal noise.
- **DirectSelect control:** direct selection of desired settings and light.
- **Silent:** maximum extractor performance with little noise
- **High grease filtration level:** filters up to 85.8% of the grease from the kitchen air.

Technical Data

Color chimney :	Stainless steel
Typology :	Chimney
Approval certificates :	CE, VDE
Length electrical supply cord (cm) :	130
Height of product, without chimney (mm) :	46
Minimum distance above an electric hob :	550
Minimum distance above a gas hob :	650
Net weight (kg) :	17.074
Type of control :	Electronic
Number of speed settings :	3-stage + 2 intensive
Maximum output air extraction (m ³ /h) :	409
Boost position output recirculating (m ³ /h) :	336
Maximum output recirculating air (m ³ /h) :	280
Boost position air extraction (m ³ /h) :	732
Number of lights :	2
Noise level (dB(A) re 1 pW) :	60
Diameter of air outlet (mm) :	120 / 150
Grease filter material :	Washable stainless steel
EAN code :	4242005099320
Connection Rating (W) :	163
Current (A) :	10
Voltage (V) :	220-240
Frequency (Hz) :	50; 60
Plug type :	GB plug
Installation typology :	Wall-mounted



Optional accessories

- DHZ1225 : Chimney extension 1000 mm
- DHZ1235 : Chimney extension 1500 mm
- DHZ5326 : Active carbon filter
- DSZ5201 : CleanAir active carbon filter spare part
- DSZ6200 : CleanAir Recirculation Kit
- DWZ0XX015 : Integrated CleanAir Recirculation Kit
- DZZ0XX0P0 : CleanAir act.carbon filter regenerative



Serie | 6, wall-mounted cooker hood, 60 cm, Stainless steel DWB68JQ50B

Wall mounted chimney hoods add style and sophistication to the kitchen and give you complete freedom in your kitchen planning.

Key performance features:

- Energy Efficiency Class: A (at a range of energy efficiency classes from A++ to E)*
- Extraction rate according to EN 61591 ø 15 cm:
max. Normal use 408 m³/h
Intensive 732 m³/h
- Noise max. Normal Level: 60 dB*

Special features

- PerfectAir sensor
- TouchControl with lightline
- 3 power levels and 2 intensive settings
- 2 x 1.5W LED light
- Colour Temperature: 3500 K
- Dimmer function
- Efficient BLDC-technology
- Automatic after running (10 min)
- Automatic intensive revert (6mins)
- 2 metal grease filter cassettes
- Saturation indicator for metal and charcoal filter
-
- easy to clean Inner frame

Design

- Brushed steel
- Box design
- Chimney extractor hood
- Designed for wall mounted installation
- Easy installation system
- TouchControl
- Electronic control

Performance/technical information

- Suitable for ducted or recirculating operation
- For recirculated extraction recirculating kit or CleanAir recirculating kit (accessory) needed
- Extraction rate according to EN 61591 ø 15 cm:
max. Normal use 408 m³/h
Intensive 732 m³/h
- Extraction rate according to EN 61591 max. 408 m³/h
- Noise level according to EN 60704-3 and EN 60704-2-13 at max. normal use exhaust air: 60 dB(A) re 1 pW (47 dB(A) re 20 µPa sound pressure)
- Noise level according to EN 60704-3 and EN 60704-2-13 exhaust air:
Max. normal use: 60 dB(A) re 1 pW (47 dB(A) re 20 µPa sound pressure)
Intensive: 73 dB(A) re 1 pW (60 dB(A) re 20 µPa sound pressure)
- Noise level according to EN 60704-3 and EN 60704-2-13 at maximum normal setting: extraction rate: 60 dB (A) re 1pW
- Noise max. Normal Level: 60 dB*
-
- Light Intensity: 267 lux
- Colour Temperature: 3500 K
- Electrical cable length 1.3 m
- Diameter pipe ø 150 mm (ø 120 mm enclosed)
- Dimensions exhaust air (HxWxD): 628-954 x 598 x 500 mm
- Dimensions recirculating (HxWxD): 628-1064 x 598 x 500 mm
- Dimensions recirculating with CleanAir module (HxWxD): 809-1139 x 598 x 500 mm
- Energy Efficiency Class: A (at a range of energy efficiency classes from A++ to E)*
- Blower Efficiency Class: A*
- Lighting Efficiency Class: A*
- Grease Filtering Efficiency Class: B*
- Average Energy Consumption: 33.7 kWh/year*

Optional accessories

- Recirculating kit

* In accordance with the EU-Regulation No 65/2014

**Serie | 6, wall-mounted cooker hood, 60 cm,
Stainless steel
DWB68JQ50B**

