
N 50. Built-in oven. Stainless steel B3ACE4HN0B









Included accessories

2 x combination grid, 1 x universal pan

Optional accessories

Z11AB15A0 Baking tray, non-stick ceramic coated

Z11CB10E0 Baking tray, grey enamelled

Z11CR10X0 Baking and roasting grid (standard)

Z11GT10X3 Glass roasting dish, 5,4l

Z11TF36X0 3 level telescopic rails, full ext

Z11TI15X0 Cliprails Z1913X0 Baking Stone

Built-in Slide&Hide® oven with fixed handle and fully retracting oven door

- $\sqrt{\mbox{ Slide\&Hide@}}$ the fully retracting oven door, unrestricted access with fixed handle.
- $\sqrt{\mbox{ CircoTherm}^{\mbox{\scriptsize @}}}$ the unique hot air-system for simultaneous baking and roasting on up to 3 levels
- $\sqrt{\mbox{ EasyClean}^{\mbox{\scriptsize @}}}$ this special cleaning aid provides uncomplicated, energy-saving cleaning of the oven interior.

- $\sqrt{}$ An environment-saving option for fast oven cleaning.
- $\sqrt{\ }$ Clip-on Rail easily removed and installed telescopic rails for flexible use on all shelf levels

Technical Data

Color / Material Front : Stainless steel

Construction type : Built-in

Integrated Cleaning system: Hydrolytic

Required niche size for installation (HxWxD) : 585-595 x 560-568 x

Dimensions of the product (mm) : $595 \times 594 \times 548$

Dimensions of the packed product (HxWxD) (mm) : $670 \times 690 \times 660$

Control Panel Material: Glass Door Material: Glass Net weight (kg): 35.030 Usable volume of cavity (I): 71

Cooking method: Bottom heat, Conventional heat, Full width grill,

Hot Air, Hotair gentle, Hot air grilling, Pizza setting

First cavity material: Other

Temperature control: No control of the temperature

Number of interior lights: 1 Approval certificates : CE, VDE

Length of electrical supply cord (cm): 120

EAN code: 4242004225164 Number of cavities (2010/30/EC): 1 Energy efficiency class (2010/30/EC): A

Energy consumption per cycle conventional (2010/30/EC): 1.04 Energy consumption per cycle forced air convection (2010/30/EC) :

Energy efficiency index (2010/30/EC): 95.3 Electrical connection rating (W): 2990

Current (A): 13 Voltage (V): 220-240 Frequency (Hz): 60; 50 Plug type: no plug



N 50, Built-in oven, Stainless steel B3ACE4HN0B

Features

Design

- LCD Display (White)
- Retractable control dials, Bevelled oval controls
- Cavity inner surface: Enamel grey
- Slide&Hide® with fixed handle
- Bar handle

Features

- Control panel lock
- Heating up indicator
- Interior halogen light
- Triple glazed door

Cleaning

- EcoClean Direct : back panel
- EasyClean
- Full glass inner door

Programmes/functions

- 7 heating methods: CircoTherm®, Top/bottom heat, Hot air grilling, Full surface grill, CircoTherm® intensive, Bottom heat, CircoTherm® gentle
- Cooling fan

Accessories

- 1 Clip rail, Stop function
- 2 x combination grid, 1 x universal pan

Performance/technical information

Energy efficiency rating (acc. EU Nr. 65/2014): A
 Energy consumption per cycle in conventional mode: 1.04 kwh
 Energy consumption per cycle in fan-forced convection mode: 0.81 kwh

Number of cavities: Main cavity Heat source: electrical Cavity volume: 71 litre


- Total connected load electric: 2.99 KW
- \bullet Temperature range 50 °C 275 °C
- Length of mains cable: 120 cm
- Nominal voltage: 220 240 V
- Appliance dimension (hxwxd): 595 mm x 594 mm x 548 mm
- Niche dimension (hxwxd): 585 mm 595 mm x 560 mm 568 mm
- Please refer to the dimensions provided in the installation manual


N 50, Built-in oven, Stainless steel B3ACE4HN0B


Dimensioned drawings

If the appliance will be installed underneath a hob, the following worktop thicknesses (including substructure if necessary) must be taken into account.

Hob type	min. worktop thickness	
	fitted	flush
Induction hob	37 mm	38 mm
Full surface Induction hob	47 mm	48 mm
Gas hob	30 mm	38 mm
Electric hob	27 mm	30 mm








measurements in mm

Installation with a hob.



measurements in mm