





- $\sqrt{}$ Compact oven with microwave even more ways to cook quickly and conveniently.
- $\sqrt{\mbox{ FullTouch Control}}$ simple, precise oven control by fingertip touch on the smooth surface of the high resolution TFT colour display.
- √ Dual cleaning options:
- $\sqrt{\,}$ Pyrolytic following heavy use just let the oven interior clean itself.
- $\sqrt{\text{EasyClean}^{\text{@}}}$ the quick and easy option for day to day maintenance.
- $\sqrt{\ }$ Hinged door with cushioned opening and closing.
- $\sqrt{}$ Home Connect rediscover your kitchen with our connected home appliances, from wherever you are.
- $\sqrt{}$ Telescopic rail pull-out for 1 level





















Z11GT10X3 Glass roasting dish, 5,4l

Z11GU20X0 Glasspan

Z11SZ00X0 SeamlessCombination mounting kit Z11SZ60X0 SeamlessCombination 45 + 14cm Z11SZ90X0 SeamlessCombination 60 + 45cm Z12CB10A0 Baking tray, anthracite enamelled Z12CM10A0 Moussaka pan, anthracite enamelled

Z12CQ10A0 Grill tray, anthracite enamelled Z13CV06S0 Decor strip Z18M45X0 Cookbook Z1913X0 Baking Stone

Technical Data

Type of micro-wave oven: MW-Combi

Type of control: Electronic

Color / Material Front : Stainless steel

Dimensions of the product (mm) : $455 \times 596 \times 548$ Cavity dimensions (mm) : 237.0 x 480 x 392.0 Length of electrical supply cord (cm): 150

Net weight (kg): 37.933 Gross weight (kg): 40.0 EAN code: 4242004236535

Maximum micro-wave power (W): 900

Connection rating (W): 3600

Current (A): 16 Voltage (V): 220-240 Frequency (Hz): 50; 60 Plug type: no plug



N 90, Built-in compact oven with microwave function, Stainless steel C28MT27H0B

Feature:

Design

- 5.7" TFT colour and graphics display with FullTouch control
- Touch control
- electronic clock
- Drop down door, SoftClose, soft opening
- Bar handle
- Cavity inner surface: Enamel anthracite

Features

- HomeConnect ready on WLAN
- Door lock during pyrolytic cleaning Control panel lock Automatic safety switch off Residual heat indicator Start button
- Temperature proposal Actual temperature display Heating up indicator Sabbath setting

Door contact switch

- Intelligent microwave inverter technology: For optimised results maximum output power will be regulated to 600 W when used in longer operation for gentler cooking.
- automatic programmes: 14
- Baking and roasting assistant, Automatic programmes
- MultiPoint MeatProbe
- LED light
- On/off button
- 3 shelf positions
- Cooling fan

Cleaning

- Pyrolytic cleaning
- EasyClean
- Microwave top door

Programmes/functions

- Compact oven with microwave with 13 heating methods: CircoTherm®, CircoTherm® Gentle, Top/bottom heat, Conventional heat Gentle, Hot air grilling, Full surface grill, Centre surface grill, CircoTherm® intensive, Bottom heat, Low temperature cooking, Dough proving, Plate warming, Keep warm
- Additional heating methods with microwave: Microwave, Microwave combination cooking
- Microwave may be used separately or in combination
- Max. Power: 900 W; 5 Microwave power settings (90 W,180 W,360 W,600 W,900 W)
- automatic programmes: 14
- Rapid heat

Standard accessories


- 1 level telescopic shelf, standard extension, pyrolitic proof
- 1 x combination grid, 1 x universal pan

Technical information


- Cavity volume: 45 l
- Temperature range 30 °C 275 °C
- Microwave inverter technology
- Length of mains cable: 150 cm
- Total connected load electric: 3.6 KW
- Nominal voltage: 220 240 V
- Appliance dimension (hxwxd): 455 mm x 596 mm x 548 mm
- Niche dimension (hxwxd): 450 mm 455 mm x 560 mm 568 mm x 550 mm
- Please refer to the dimensions provided in the installation manual

N 90, Built-in compact oven with microwave function, Stainless steel C28MT27H0B


Dimensioned drawings



measurements in mm



Installation with a hob.



measurements in mm

If the compact appliance will be installed underneath a hob, the following worktop thicknesses (including substructure if necessary) must be taken into account.

Hob type	min. work	min. worktop thickness	
	fitted	flush	
Induction hob	42 mm	43 mm	
Full surface Induction hob	52 mm	53 mm	
Gas hob	32 mm	43 mm	
Electric hob	32 mm	35 mm	