

N 30, canopy cooker hood, 53 cm, Silver metallic
D5655X1GB



COOKING PASSION SINCE 1877



C



Canopy hood: designed to fit neatly under an overhead unit or cabinet. They're discreet and effectively use valuable space.

- ✓ LED lighting: a clear illumination whilst cooking thanks to the energy-saving LED lights
- ✓ Intensive speed setting: increases the extraction rate when the steam gets intense
- ✓ High extraction rate: Ensures a clear view while cooking thanks to efficient motor technology as either a ducted or recirculating solution.

Features

Technical Data

Typology : Traditional
Approval certificates : CE, VDE
Length electrical supply cord (cm) : 130
Required niche size for installation (HxWxD) : 255mm x 500mm x 350mm
Minimum distance above an electric hob : 650
Minimum distance above a gas hob : 650
Net weight (kg) : 7.439
Type of control : mechanical
Maximum output air extraction (m³/h) : 363
Boost position output recirculating (m³/h) : 395
Maximum output recirculating air (m³/h) : 268
Boost position air extraction (m³/h) : 618
Number of lights : 2
Noise level (dB(A) re 1 pW) : 56
Diameter of air outlet (mm) : 150 / 120
Grease filter material : Washable aluminium
EAN code : 4242004237136
Connection Rating (W) : 206
Current (A) : 10
Voltage (V) : 220-240
Frequency (Hz) : 50
Plug type : GB plug
Installation typology : Built-in

Optional accessories

Z5155X0 Accessories extractor hoods



4 242004 237136

N 30, canopy cooker hood, 53 cm, Silver metallic

D5655X1GB

Features

Key performance features:

- Energy Efficiency Class: C (at a range of energy efficiency classes from A++ to E)*
- Extraction rate according to EN 61591 ø 15 cm:
max. Normal use 360 m³/h
Intensive 590 m³/h
- Noise max. Normal Level: 56 dB*

Features

- Slide control operation
- 3 speeds plus intensive
- 2 x LED spot 2.15W (low volt)
- Colour Temperature: 3500 K
- 2 metal grease filter cassettes

Design

- For installation in a chimney or unit, above a hob
- Silver metallic grey
- Canopy hood
- Slide control operation
- Mechanical controls

Performance/technical information

- Suitable for ducted extraction and recirculation
- For recirculated extraction charcoal filter (accessory) needed
- Max. extraction rate: 590 m³/h
- Extraction rate according to EN 61591 ø 15 cm:
max. Normal use 360 m³/h
Intensive 590 m³/h
- Noise max. Normal Level: 56 dB*
- Noise level according to EN 60704-3 and EN 60704-2-13 exhaust air:
Max. normal use: 56 dB(A) re 1 pW (44 dB(A) re 20 µPa sound pressure)
Intensive: 68 dB(A) re 1 pW (56 dB(A) re 20 µPa sound pressure)
-
- Light Intensity: 438 lux
- Colour Temperature: 3500 K
- Electrical cable length 1.3 m
- Diameter pipe ø 150 mm (ø 120 mm enclosed)
- Dimensions exhaust air (HxWxD): 255-255 x 530 x 380 mm
- Dimensions recirculating (HxWxD): 255-255 x 530 x 380 mm
- Mounting dimensions: width: 50 cm, depth: 35 cm
- Energy Efficiency Class: C (at a range of energy efficiency classes from A++ to E)*
- Blower Efficiency Class: D*
- Lighting Efficiency Class: A*
- Grease Filtering Efficiency Class: C*
- Average Energy Consumption: 78.1 kWh/year*

Optional accessories

- Recirculating kit
- * In accordance with the EU-Regulation No 65/2014

N 30, canopy cooker hood, 53 cm, Silver metallic
D5655X1GB

Dimensioned drawings

