

N 50, wall-mounted cooker hood, 60 cm, clear glass black printed
D651HM1S0B



B



The sleek black glass design angled hood ensures your kitchen is free from cooking smells thanks to advanced features which let you get on with your cooking

- ✓ TouchControl: thanks to the integrated flat surface of the control panel, adjustments can be easily made with just one finger
- ✓ Intensive speed setting: increases the extraction rate when the steam gets intense
- ✓ LED lighting: a clear illumination whilst cooking thanks to the energy-saving LED lights

Features

Technical Data

Color chimney : Stainless steel
 Typology : Chimney
 Approval certificates : CE, VDE
 Length electrical supply cord (cm) : 130
 Height of product, without chimney (mm) : 323
 Minimum distance above an electric hob : 450
 Minimum distance above a gas hob : 600
 Net weight (kg) : 18.368
 Type of control : Electronic
 Maximum output air extraction (m³/h) : 416
 Boost position output recirculating (m³/h) : 557
 Maximum output recirculating air (m³/h) : 388
 Boost position air extraction (m³/h) : 700
 Number of lights : 2
 Noise level (dB(A) re 1 pW) : 58
 Diameter of air outlet (mm) : 120 / 150
 Grease filter material : Washable aluminium
 EAN code : 4242004210030
 Connection Rating (W) : 263
 Current (A) : 10
 Voltage (V) : 220-240
 Frequency (Hz) : 60; 50
 Plug type : GB plug
 Installation typology : Wall-mounted



4 242004 210030

Optional accessories

Z50XP0X0	CleanAir act.carbon filter regenerative
Z5170X1	CleanAir active carbon filter spare part
Z51AIA0X0	Active carbon filter (spare part)
Z51AIROX0	Recirculation kit regenerative chimless
Z51AIS0X0	Recirculation kit regenerative
Z51AIT0X0	Recirculation kit for chimless use
Z51AIU0X0	Recirculation kit
Z51AXK0N0	Chimney extension 1000 mm
Z51AXL0N0	Chimney extension 1500 mm

*N 50, wall-mounted cooker hood, 60 cm, clear
glass black printed
D651HM1S0B*

Features

Key performance features:

- Energy Efficiency Class: B (at a range of energy efficiency classes from A++ to E)*
- Extraction rate according to EN 61591 ø 15 cm:
max. Normal use 416 m³/h
Intensive 700 m³/h
- Noise max. Normal Level: 58 dB*

Features

- Touch control
- LED display
- 3 speeds plus intensive
- 2 x 1.5w LED Light
- Colour Temperature: 3500 K
- Automatic intensive revert (6mins)
- 2 metal grease filter cassettes
- easy to clean Inner frame
- For wall mounted installation
- Rim ventilation

Design

- Black Glass
- Angled glass design
- Chimney hood
- Touch control
- Electronic controls

Performance/technical information

- Suitable for ducted extraction and recirculation
- For recirculated extraction recirculating kit or CleanAir recirculating kit (accessory) needed
- Easy installation system
- Extraction rate according to EN 61591 ø 15 cm:
max. Normal use 416 m³/h
Intensive 700 m³/h
- Extraction rate according to EN 61591 max. 416 m³/h
- Noise level according to EN 60704-3 and EN 60704-2-13 at max. normal use exhaust air: 58 dB(A) re 1 pW (45 dB(A) re 20 µPa sound pressure)
- Noise level according to EN 60704-3 and EN 60704-2-13 exhaust air:
Max. normal use: 58 dB(A) re 1 pW (45 dB(A) re 20 µPa sound pressure)
Intensive: 67 dB(A) re 1 pW (54 dB(A) re 20 µPa sound pressure)
- Noise level according to EN 60704-3 and EN 60704-2-13 at maximum normal setting: extraction rate: 58 dB (A) re 1pW
- Noise max. Normal Level: 58 dB*
-
- Light Intensity: 100 lux
- Colour Temperature: 3500 K
- Electrical cable length 1.3 m
- Diameter pipe Ø 150 mm (Ø 120 mm enclosed)
- Dimensions exhaust air (HxWxD): 928-1198 x 590 x 499 mm
- Dimensions recirculating (HxWxD): 988-1258 x 590 x 499 mm
- Dimensions recirculating with CleanAir module (HxWxD):
1118 x 590 x 499 mm - mounting with outer chimney
1188-1458 x 590 x 499 mm - mounting with telescopic chimney
- Energy Efficiency Class: B (at a range of energy efficiency classes from A++ to E)*
- Blower Efficiency Class: B*
- Lighting Efficiency Class: B*
- Grease Filtering Efficiency Class: C*
- Average Energy Consumption: 56.6 kWh/year*

Optional accessories

- Recirculating kit

* In accordance with the EU-Regulation No 65/2014