











The gas hob with a stainless-steel surface design and adjustable FlameSelect.

- $\sqrt{\ }$ FlameSelect Thanks to the clever control of gas flow, the flame can be precisely adjusted in 9 steps. Always the same reliable and precise power levels for outstanding cooking convenience.
- $\sqrt{}$ Continuous cast-iron pan supports for maximum stability and cooking convenience.

Feature

Technical Data

Product name/family : gas hob w integrated controls

Construction type : Built-in

Energy input : Gas

Total number of positions that can be used at the same time : 4 Required niche size for installation (HxWxD) : $45 \times 560-562 \times 10^{-2}$

480-492

Width of the product (mm): 582

Dimensions of the product (mm) : $45 \times 582 \times 520$

Dimensions of the packed product (HxWxD) (mm) : $141 \times 651 \times 578$

Net weight (kg): 11.423 Gross weight (kg): 12.0 Residual heat indicator: without Location of control panel: Hob front Basic surface material: Stainless steel Color of surface: Stainless steel Color of frame: Stainless steel Approval certificates: CE, Eurasian Length of electrical supply cord (cm): 100

EAN code: 4242004203438 Electrical connection rating (W): 1 Gas connection rating (W): 8000

Current (A): 3 Voltage (V): 220-240 Frequency (Hz): 60; 50



N 70, Gas hob, 60 cm, T26DS59N0

Features

Design

• Stainless steel

Special features

- FlameSelect with 9 steps
- Design co-ordinated control dials
- Ignition via control dials
- black cast iron pan supports with protective rubber feet

Power and size:

- 4 burner hob
- 3 gas + wok
- Left rear: Standard burner 1.75 KW
- Right rear: WOK burner 3.5 KW
- Left front: Standard burner 1.75 KW
- Right front: Economy burner 1 KW

Safety Features

- Flame failure safety device
- Factory set for connection to mains gas

Technical information

• Power cord length 100 cm

Accessories

• LPG jets (28-30/37mbar) included

Dimensioned drawings

