


COOKING PASSION SINCE 1877





- $\sqrt{\ }$ FlameSelect Thanks to the clever control of gas flow, the flame can be precisely adjusted in 9 steps. Always the same reliable and precise power levels for outstanding cooking convenience.
- √ 7-segment display with residual heat indicator Provides a digital display of the power level selected for a particular cooking zone. After the hob is turned off, the indicator informs you of the cooking zone's residual heat.
- $\sqrt{}$ Powerful cooking at up to 4 kW.
- $\sqrt{}$ Extremely easy-to-clean glass surface.
- $\sqrt{}$ You have the option of installing the gas hob either flush or surface mounted.







Optional accessories

Z2471X0 Wok ring

Feature

Technical Data

Product name/family : gas hob w integrated controls

Construction type : Built-in

Energy input: Gas

Total number of positions that can be used at the same time : 5 Required niche size for installation (HxWxD) : $45 \times 560-562 \times 10^{-2}$

480-492

Width of the product (mm): 752

Dimensions of the product (mm) : $45 \times 752 \times 520$

Dimensions of the packed product (HxWxD) (mm) : $145 \times 793 \times 597$

Net weight (kg): 19.827 Gross weight (kg): 21.0

Residual heat indicator : Separate Location of control panel : Hob front Basic surface material : Hard Glass

Color of surface : Black Color of frame : Black Approval certificates : CE

Length of electrical supply cord (cm): 100

EAN code: 4242004183167 Electrical connection rating (W): 2 Gas connection rating (W): 11500

Current (A) : 3 Voltage (V) : 220-240 Frequency (Hz) : 60; 50



N 70, Gas hob, 75 cm, T27CA59S0

Features

Design

• black tempered glass

Special features

- FlameSelect with 9 steps
- LED display for each zone
- Design co-ordinated control dials
- Ignition via control dials
- Cast iron pan supports with rubber feet

Power and size:

- 5 burner hob
- 4 gas + wok (Center)
- Left rear: Standard burner 1.75 KW
- Right rear: High speed burner 3 KW
- Center: Wok burner 4 KW
- Left front: Economy burner 1 KW
- Right front: Standard burner 1.75 KW

Safety Features

- Flame failure safety device
- 1 stage
- Factory set for connection to mains gas


Technical information


• Power cord length 100 cm

Accessories

• LPG jets (28-30/37mbar) included

Dimensioned drawings





measurements in mm