

D303130 Amalfi™ Two Handle Widespread Lavatory Faucet

SPECIFICATIONS

Features/Benefits

- 1.2 gpm (4.5 L/min) Max Flow @ 60 psi with Laminar Water Stream
- Alternative Flow Rates Available with Spray Water Stream
 - 1.0 gpm (3.8 L/min) When Used with DA613094N Aerator
 - 0.5 gpm (1.9 L/min) When Used with DA613093N Aerator
- 7 9/16" Spout Height, 3 9/16" Spout Reach
- Ceramic Disc Cartridge
- Includes Metal Touch-Down Drain Assembly
- 3-Hole Mount
- 6"- 12" Installation



Location:



Chrome

Please see danze.com or current price list for available finishes. Finish is defined by additional suffix.

Mount Type

6"-12

Standards & Certifications



Ready Creating

4 7/8" 9 1/8"~13 1/8" (124mm) (232~333mm) 3 9/16" 6"~12" (90mm) (152~304mm) (192mm) 2 5/16" (58mm) <u>1/2"Min</u> (12.7mm) 7 9/16" 1/4"Max 21 (32mm) Ø 2 1/8" 106mm) (Ø 54mm) 4 3/16" J Ø 1 7/8" . (Ø 48mm) 76mm Ø 1 7/8' M40X1.5 (Ø 48mm) 1 1/8"-20UN 1/2"Max (64mm) (220mm) 8 3/4" 6 1/2" (165mm) 1 1/2"~2 1/4" (38~57mm) (32~64mm) 1/4"~2 1/2" 5/8"-18UNF 日日 1/2"-14NPSM Ø 1 1/4" Ø 1"- Ø 1 1/2" Ø 1 5/16" - Ø 1 1/2" (Ø 31.75mm) (Ø 25mm - Ø 38mm) Hole Size (Ø 33mm - Ø 38mm) Hole Size Submittal Information: Name: Contractor:

> WARRANTY: Danze products are covered by a manufacturer's lifetime limited warranty for manufacturing defects. Danze, Inc., 2500 Internationale Parkway, Woodridge, IL 60517, USA www.danze.com

Contact #: