



PRODUCT DESCRIPTION

By uniting a romantic shape with a stunning circle of brilliant light, we created an Eternity™ that encapsulates a clear vision of renewal and balance, boldly illuminating your space with timeless elegance.

SPECIFICATION STATEMENT

Solution shall consist of a lighted mirror with forward-facing task lighting. Mirror shall have corrosion-resistant glass and have uniform light output in frosted areas, using dimmable, replaceable LEDs with greater than or equal to 90 CRI (color rendering index). Product will be made in USA and have a 7-year limited warranty.

THE ELECTRIC MIRROR ADVANTAGE

- ☑ Global mirror technology leader for over 20 years
- ☑ More installations than all competitors combined
- ☑ Realistic warranty you can believe in and trust
- ☑ Lowest total cost of ownership
- ☑ U.S. based customer service support
- ☑ Onsite quality management

FEATURES AND BENEFITS

- Copper-free, corrosion-resistant DuraMirror™ glass
- Forward-facing task lighting
- Environmentally sustainable
- Energy efficient
- Fast lead times
- Easy installation
- Title 24 compliant
- 7-year limited warranty
- Covered by one or more patents
- Proudly made in the USA

AVAILABLE OPTIONS

- Ava™ SmartLook™ Technology¹

LIGHTING SPECIFICATIONS

- Natural-looking LED light color
- Forward-phase, dimmable, replaceable LEDs
- CRI: 90+
- CCT: 3,000 Kelvin (Without Ava)
- CCT: 2,700/4,600/6,500 Kelvin (With Ava)
- 869 lumens per foot
- Calculated L₇₀ 52,000-hour LED lifespan
- Maximum 100 lumens per watt efficacy

SAFETY SPECIFICATIONS

- Entire assembly meets UL/cUL standards
- International certifications
- Safety-backed mirror

¹ See technology specification sheets for more information.

INSTALLATION SPECIFICATIONS

- 120V-240V hardwire electrical connection; provide 36" whip; junction box not required
- Chassis should be mounted to wall studs; mounting holes are provided
- For Eternity without Ava, fixture can be controlled by an on/off switch or forward-phase dimming switch
- For Eternity with Ava, fixture can be controlled by an on/off switch or by using Ava touch control, located on the mirror 6" up from the bottom border
- Mirror must be installed in the orientation shown below

MODELS

Base Model	Base Model with Ava	Dimensions	Power Requirements
ETE-2130	ETE-2130-AE	21"W x 30"H x 1.75"D (533mm x 762mm x 44mm)	120/240 VAC, 58W
ETE-30	ETE-30-AE	30" diameter x 1.75"D (762mm x 44mm)	120/240 VAC, 75W
ETE-36	ETE-36-AE	36" diameter x 1.75"D (914mm x 44mm)	120/240 VAC, 94W

*Base model number shown only. To specify additional options, contact Electric Mirror at residential@electricmirror.com

DIMENSIONAL DRAWING (Not to scale. Frost and border widths may vary depending on mirror size.)

