WATER











Built Tough and Ready to Serve

- Polished stainless steel cylinder complete with protective skirt
- Chrome-plated solid brass valve
- Waterproof stainless steel gauge
- Stainless steel handles and siphon tube
- Oversized stainless steel pull pin with retaining strap for easier and faster activation
- Color and bar-coded labels for accurate service
- Shipped empty without pressure
- Schrader valve for pressurizing
- Complies with NFPA 10 Standard
- Meets D.O.T. Requirements
- Temperature range: 40°F to 120°F (4°C to 49°C)

STRIKE FIRST Water
Fire Extinguishers are designed for:





MEETS OR EXCEEDS:

ANSI/UL 626 & 711



MEETS OR EXCEEDS:

CAN/ULC-S507 & S508







The STRIKE FIRST water extinguisher is an ideal choice for Class A fire hazards. The powerful stream of water allows it to reach areas other extinguishers cannot.

An effective extinguisher for Class A fires in areas such as warehouse, agriculture and industrial locations.

CAPACITY	2.4 GALLONS (9L)
Model No.	SF-PW250
UL/ULC Rating	2-A
Range	40 ft (12.2 m)
Discharge Time	55 sec
PSI	100
Height	25" (63.5 cm)
Width	8 3/4" (22 cm)
Diameter	7 1/8" (18 cm)
Weight	7.9 lbs (3.6 kg)
Standard Bracket	Wall