

Dyna-Glo

2023-2024

CONSTRUCTION HEATERS WAREHOUSE CATALOG



**KEROSENE FORCED AIR | LIQUID PROPANE FORCED AIR | TANK TOP | CONVECTION
TORCH | LARGE RADIANT | OVERHEAD INFRARED HEATERS | UNIT HEATERS**



INDEX

Kerosene Forced Air	4
Liquid Propane Forced Air	6
Tank Top	9
Convection	10
Large Radiant / Torch	12
Overhead Infrared	13
Gas Unit	14



MODEL NUMBER: KFA50DGD
BTU: 50,000
 ☒ HEATS UP TO 1,200 SQ.FT.



- Easy Lift Carrying Handle
- Run Time Fuel Gauge
- Fuel Capacity: 5 Gallons
- Heating Hours: 13 Hours
- Flameout Sensor
- Temperature Limit Control

MODEL NUMBER: KFA80DGD
BTU: 80,000
 ☒ HEATS UP TO 1,900 SQ.FT.



- Comfort Control Thermostat
- Run Time Fuel Gauge
- Fuel Capacity: 5 Gallons
- Heating Hours: 9 Hours
- Easy Lift Carrying Handle & Cord Wrap
- Flameout Sensor

MODEL NUMBER: KFA220DGD
BTU: 180,000 OR 220,000
 ☒ HEATS UP TO 5,200 SQ.FT.



- Dual Heat Technology
- Comfort Control Thermostat
- Fuel Capacity: 13 Gallons
- Heating Hours: 8 - 10 Hours
- Dual Source Power Cord
- Built in Digital Diagnostics

MODEL NUMBER: KFA400DGD
BTU: 400,000
 ☒ HEATS UP TO 8,500 SQ.FT.



- Comfort Control Thermostat
- Built in Digital Display
- Fuel Capacity: 29 Gallons
- Heating Hours: 9.5 Hours
- Flameout Sensor
- Sturdy, Rugged Construction

MODEL NUMBER: KFA135DGD
BTU: 95,000 OR 135,000
 ☒ HEATS UP TO 3,200 SQ.FT.



- Dual Heat Technology
- Comfort Control Thermostat
- Fuel Capacity: 10 Gallons
- Heating Hours: 10-14 Hours
- Run Time Fuel Gauge
- Built in Digital Diagnostics

MODEL NUMBER: KFA180DGD
BTU: 140,000 OR 180,000
 ☒ HEATS UP TO 4,200 SQ.FT.



- Dual Heat Technology
- Comfort Control Thermostat
- Fuel Capacity: 13 Gallons
- Heating Hours: 10-12 Hours
- Run Time Fuel Gauge
- Built in Digital Diagnostics

MODEL NUMBER: KFA650DGD
BTU: 650,000
 ☒ HEATS UP TO 13,500 SQ.FT.



- Comfort Control Thermostat
- Built in Digital Display
- Fuel Capacity: 50 Gallons
- Heating Hours: 10 Hours
- Outdoor and Indoor Construction/Commercial with proper ventilation
- Exclusive - Run Time Fuel Gauge

MODEL NUMBER: SF70DGD
BTU: 70,000
 ☒ HEATS UP TO 1,700 SQ.FT.



- Dual Heat Technology
- Comfort Control Thermostat
- Fuel Capacity: 4 Gallons
- Heating Hours: 8 Hours
- Run Time Fuel Gauge
- Dual Source Power Cord

MODEL NUMBER: RMC-FA40DGD
BTU: 40,000
 ☒ HEATS UP TO 1,000 SQ.FT.



- Adjustable Heat Angle
- One Hand Piezo Ignition
- Overheat Auto Shut-off Protection
- Includes 10' Hose & Regulator
- Sturdy, Rugged Construction
- 20, 40, or 100 LB. Propane (LP) Cylinder Requires for Operation - Not Included

MODEL NUMBER: LPFA43DGD
BTU: 37,000-43,000
 ☒ HEATS UP TO 1,100 SQ.FT.



- One Hand Piezo Ignition
- Overheat Auto Shut-off Protection
- Includes 10' Hose & Regulator
- 20lb Tank Runtime: 10-12 Hours
- 20, 40, or 100 LB. Propane (LP) Cylinder Requires for Operation - Not Included
- Easy Lift Carrying Handle

MODEL NUMBER: RMC-FA125DGD
BTU: 70,000 - 125,000
 ☒ HEATS UP TO 3,100 SQ.FT.



- Continuously Variable BTUs
- Continuous Electronic Ignition - Prevents Dangerous Delayed Ignition
- Overheat Auto Shut-off Protection
- 40lb Tank Runtime: 7-14 Hours
- Includes 10' Hose & Regulator
- Adjustable Heat Angle

MODEL NUMBER: LPFA125Q
BTU: 70,000 - 125,000
 ☒ HEATS UP TO 3,100 SQ.FT.



- Continuously Variable BTUs
- Continuous Electronic Ignition - Prevents Dangerous Delayed Ignition
- On/Off Switch
- 40lb Tank Runtime: 7-12 Hours
- Includes 10' Hose & Regulator
- Adjustable Heat Angle

MODEL NUMBER: RMC-FA60DGD
BTU: 30,000 - 60,000
 ☒ HEATS UP TO 1,350 SQ.FT.



- Adjustable Heat Angle
- Continuous Electronic Ignition - Prevents Dangerous Delayed Ignition
- Overheat Auto-Shut-off Protection
- Includes 10' Hose & Regulator
- 20lb Tank Runtime: 7-14 Hours
- 20, 40, or 100 LB. Propane (LP) Cylinder Requires for Operation - Not Included

MODEL NUMBER: LPFA60Q
BTU: 36,000 - 60,000
 ☒ HEATS UP TO 1,350 SQ.FT.



- Continuously Variable BTUs
- Continuous Electronic Ignition - Prevents Dangerous Delayed Ignition
- On/Off Switch
- 20lb Tank Runtime: 7-14 Hours
- Includes 10' Hose & Regulator
- Adjustable Heat Angle

MODEL NUMBER: RMC-FA150DGD
BTU: 120,000 - 150,000
 ☒ HEATS UP TO 3,500 SQ.FT.



- Comfort Control Thermostat
- Continuously Variable BTUs
- Continuous Electronic Ignition - Prevents Dangerous Delayed Ignition
- Overheat Auto Shut-off Protection
- 40lb Tank Runtime: 6-7 Hours
- Includes 10' Hose & Regulator

MODEL NUMBER: RMC-FA150NGDGD
BTU: 150,000
 ☒ HEATS UP TO 3,000 SQ.FT.



- Natural Gas
- Comfort Control Thermostat
- Direct Discharge Spark, Interrupted
- Overheat Auto-Shut-off Protection
- Adjustable Heat Angle
- Sturdy, Rugged Construction
- Easy Lift Carrying Handle

MODEL NUMBER: RMC-FA300DGD
BTU: 300,000
 ☒ HEATS UP TO 7,000 SQ.FT.



- Continuous Electronic Ignition - Prevents Dangerous Delayed Ignition
- Overheat Auto-Shut-off Protection
- 40lb Tank Runtime: 3 Hours
- Includes 10' Hose & Regulator
- Adjustable Heat Angle



MODEL NUMBER: TT15CDGP
BTU: 9,000 - 15,000
 ☒ HEATS UP TO 15 FT. RADIUS



Tank not included

- Variable BTUs
- Hi-efficiency Steel Heat Reflector
- Rust Proof Chrome Emitter Guard
- Porcelain Coated Back with Rear Safety Grill
- Tip Over Safety Switch
- Match Light Ignition
- Safety Shut-off Valve -Stops Gas Flow if Flame is Extinguished

MODEL NUMBER: TT30CDGP
BTU: 9,000 - 30,000
 ☒ HEATS UP TO 25 FT. RADIUS



Tank not included

- Variable BTUs
- Hi-efficiency Steel Heat Reflector
- Rust Proof Chrome Emitter Guard
- Porcelain Coated Back with Rear Safety Grill
- Tip Over Safety Switch
- Match Light Ignition
- Safety Shut-off Valve -Stops Gas Flow if Flame is Extinguished

MODEL NUMBER: TT360DG (4/MASTER)
BTU: 30,000 - 40,000
 ☒ HEATS UP TO 1,000 SQ.FT.



Tank not included

- Variable BTUs
- Hi-efficiency Steel Heat Reflector
- Rust Proof Chrome Emitter Guard
- Match Light Ignition
- Safety Shut-off Valve -Stops Gas Flow if Flame is Extinguished
- Quick Connect P.O.L Tank Connection - fits most 20 LB. Propane Tanks



MODEL NUMBER: RA18LPDG
BTU: 6,000 - 18,000
 ☒ HEATS UP TO 600 SQ.FT.



- Piezo Ignition with Heat Controls
- Side Carry Handles
- 3 Plaque Heating System
- Front Safety Grill
- Oxygen Depletion Sensor (ODS)
- Locking Casters

MODEL NUMBER: RMC-55R7
BTU: 10,000
 ☒ HEATS UP TO 500 SQ.FT.



- No electricity needed
- Save on utility bills
- Dependable - Ideal for emergency use or daily use
- Economical - Cut heating bills by warming only occupied areas
- Convenient - Easy to use automatic ignition and one-touch shut-off
- Safe - Built-in safety switch shuts power off if unit is knocked over

MODEL NUMBER: RMC-55R7B
BTU: 10,000
 ☒ HEATS UP TO 500 SQ.FT.



- No electricity needed
- Save on utility bills
- Dependable - Ideal for emergency use or daily use
- Economical - Cut heating bills by warming only occupied areas
- Convenient - Easy to use automatic ignition and one-touch shut-off
- Safe - Built-in safety switch shuts power off if unit is knocked over



MODEL NUMBER: RMC-LPC25DG
BTU: 15,000 - 25,000
 ☒ HEATS UP TO 600 SQ.FT.



- Outdoor and Indoor Construction/Commercial with proper ventilation
- Continuously Variable BTUs
- 360° Heat Radius
- Inner Windshield
- Includes 10-foot Hose and Regulator
- Auto Safety Shutoff

MODEL NUMBER: RMC-LPC80DG
BTU: 50,000 - 80,000
 ☒ HEATS UP TO 2,000 SQ.FT.



- Outdoor and Indoor Construction/Commercial with proper ventilation
- Continuously Variable BTUs
- 360° Heat Radius
- Inner Windshield
- Includes 10-foot Hose and Regulator
- 2-piece Knockdown Burn Chamber

MODEL NUMBER: RMC-LPC200DG
BTU: 50,000 - 200,000
 ☒ HEATS UP TO 4,700 SQ.FT.



- Outdoor and Indoor Construction/Commercial with proper ventilation
- Continuously Variable BTUs
- 360° Heat Radius
- Inner Windshield
- Includes 10-foot Hose and Regulator
- 2-piece Knockdown Burn Chamber



MODEL NUMBER: RA100NGDGD
BTU: 50,000 - 100,000
 ☒ HEATS UP TO 2,900 SQ.FT.



- Outdoor and Indoor Construction/Commercial with proper ventilation
- Variable BTUs (L/M/H settings)
- 360° Heat Radius
- Safety Tip Over Switch
- Large sturdy Base Prevents Tipping
- No Electricity Required
- Operates on Natural Gas Only

MODEL NUMBER: RA250NGDGD
BTU: 250,000
 ☒ HEATS UP TO 5,900 SQ.FT.



- Outdoor and Indoor Construction/Commercial with proper ventilation
- Variable BTUs (L/M/H settings)
- 360° Heat Radius
- Includes 15-foot Hose and Regulator
- Safety Tip Over Switch
- Large sturdy Base Prevents Tipping
- Operates on Natural Gas Only

MODEL NUMBER: RA125LPDGD
BTU: 50,000 - 125,000
 ☒ HEATS UP TO 2,900 SQ.FT.



- Outdoor and Indoor Construction/Commercial with proper ventilation
- Variable BTUs (L/M/H settings)
- 360° Heat Radius
- Includes 15-foot Hose and Regulator
- Safety Tip Over Switch
- Large sturdy Base Prevents Tipping
- No Electricity Required

MODEL NUMBER: LPT500DG
BTU: 500,000



- No Electricity Needed
- Includes 10ft. Hose and Striker to start
- Ergonomic Grip Handle
- Quality Handle makes it easier to control

MODEL NUMBER: OHIR18LV
BTU: 18,000
 ☒ HEATS UP TO 450 SQ FT



- No Electricity Required
- Adjustable Thermostat Included
- Multi-Position Ceiling Mount Included
- High Efficiency Directional Heating
- Piezo Ignition
- Wall Switch Compatible

MODEL NUMBER: OHIR30NV
BTU: 30,000
 ☒ HEATS UP TO 750 SQ FT



- No Electricity Required
- Adjustable Thermostat Included
- Multi-Position Ceiling Mount Included
- High Efficiency Directional Heating
- Piezo Ignition
- Wall Switch Compatible

MODEL NUMBER: OHIR22NV
BTU: 22,000
 ☒ HEATS UP TO 550 SQ FT



- No Electricity Required
- Adjustable Thermostat Included
- Multi-Position Ceiling Mount Included
- High Efficiency Directional Heating
- Piezo Ignition
- Wall Switch Compatible

MODEL NUMBER: OHIR33NV
BTU: 33,000
 ☒ HEATS UP TO 825 SQ FT



- No Electricity Required
- Adjustable Thermostat Included
- Multi-Position Ceiling Mount Included
- High Efficiency Directional Heating
- Piezo Ignition
- Wall Switch Compatible

MODEL NUMBER: GUH50NE/LE
BTU: 50,000
⊗ **HEATS UP TO 1600 SQ FT**



- Able to be used with NG or LP
- Conversion Kit Included
- Power exhaust allows for vertical or horizontal venting
- Can be installed in low-ceiling buildings

MODEL NUMBER: GUH80NE/LE
BTU: 80,000
⊗ **HEATS UP TO 2,000 SQ FT**



- Able to be used with NG or LP
- Conversion Kit Included
- Power exhaust allows for vertical or horizontal venting
- Can be installed in low-ceiling buildings



6440 W Howard St
Niles, IL 60714-3302

(877) 447-4768
www.ghpgroupinc.com