

XRC135-VSB250

Description	Lead free Xray protective material designed for use as shielding where high strength is required.	
Product Features	Skinned lead free vinyl	
Physical Properties	Composition	Vinyl matrix
	Color	Sky Blue
	Lead equivalence	0.250 mm +/- 10%
	Thickness	1.40 mm +/-0.1
	Weight	3.5 kg/m²
	Hardness	40 +/- 5 Shore A
	Tensile strength (min.)	6 MPa
	Elongation	NA
	Elongation at Break	250% min
	Temperature resistance	-40°C to +70°C
Disclaimer	<p>The information in this data sheet is a result of many years of experience. The details of the product are general statement, and the suitability of the material for a specific application is subject to tests on such applications.</p> <p>The performance of the material when in contact with acids, alkalis and other chemicals may depend on the concentrations and temperatures involved. It may be necessary to perform practical tests.</p> <p>Applications where the material is subject to temperature extremes should be checked by practical tests.</p> <p>Some variations to the physical data given in the data sheet are possible. Refer to our Terms and Conditions concerning liability.</p>	
Manufacturer	Lead Free Shields	

Questions regarding the details of this product should be directed to:

Lead Free Shields
4747 Research Forest Dr
Ste 180 #139
The Woodlands, TX 77381

Tel: (832) 519-8787
Email: sales@leadfreeshields.com
Web: www.xraycurtains.com