

**XRC683-NYL025**

<b>Description</b>	Leaded Xray protective curtain designed for use in medical, dental, veterinary, and industrial applications.	
<b>Product Features</b>	<b>Lightweight leaded vinyl core</b> <b>Protective nylon outer layer</b> <b>Grommets every 6" on top edge</b>	
<b>Physical Properties</b>	<b>Composition</b>	<b>Vinyl matrix, nylon outer</b>
	<b>Color</b>	<b>Various outer colors available</b>
	<b>Lead equivalence</b>	<b>0.25 mm +/- 10%</b>
	<b>Thickness</b>	<b>1.0 mm +/- 10%</b>
	<b>Weight</b>	<b>3 kg/m<sup>2</sup></b>
	<b>Tensile strength (min.)</b>	<b>6 MPa</b>
	<b>Temperature resistance</b>	<b>-40°C to +70°C</b>
<b>Disclaimer</b>	<p>The information in this data sheet is a result of many years of experience. The details of the product are general statement, and the suitability of the material for a specific application is subject to tests on such applications.</p> <p>The performance of the material when in contact with acids, alkalis and other chemicals may depend on the concentrations and temperatures involved. It may be necessary to perform practical tests.</p> <p>Applications where the material is subject to temperature extremes should be checked by practical tests.</p> <p>Some variations to the physical data given in the data sheet are possible. Refer to our terms and conditions concerning liability.</p>	
<b>Manufacturer</b>	Lead Free Shields	

**Questions regarding the details of this product should be directed to:**

**Lead Free Shields**  
**4747 Research Forest Dr**  
**Ste 180 #139**  
**The Woodlands, TX 77381**

**Tel: (832) 519-8787**  
**Email: [sales@leadfreeshields.com](mailto:sales@leadfreeshields.com)**  
**URL: [www.xraycurtains.com](http://www.xraycurtains.com)**

# XRC683-NYL050

<b>Description</b>	Leaded Xray protective curtain designed for use in medical, dental, veterinary, and industrial applications.														
<b>Product Features</b>	<b>Lightweight leaded vinyl core</b> <b>Protective nylon outer layer</b> <b>Grommets every 6" on top edge</b>														
<b>Physical Properties</b>	<table border="1"><tr><td><b>Composition</b></td><td><b>Vinyl matrix, nylon outer</b></td></tr><tr><td><b>Color</b></td><td><b>Various outer colors available</b></td></tr><tr><td><b>Lead equivalence</b></td><td><b>0.5 mm +/- 10%</b></td></tr><tr><td><b>Thickness</b></td><td><b>2.0 mm +/- 10%</b></td></tr><tr><td><b>Weight</b></td><td><b>6 kg/m<sup>2</sup></b></td></tr><tr><td><b>Tensile strength (min.)</b></td><td><b>6 MPa</b></td></tr><tr><td><b>Temperature resistance</b></td><td><b>-40°C to +70°C</b></td></tr></table>	<b>Composition</b>	<b>Vinyl matrix, nylon outer</b>	<b>Color</b>	<b>Various outer colors available</b>	<b>Lead equivalence</b>	<b>0.5 mm +/- 10%</b>	<b>Thickness</b>	<b>2.0 mm +/- 10%</b>	<b>Weight</b>	<b>6 kg/m<sup>2</sup></b>	<b>Tensile strength (min.)</b>	<b>6 MPa</b>	<b>Temperature resistance</b>	<b>-40°C to +70°C</b>
<b>Composition</b>	<b>Vinyl matrix, nylon outer</b>														
<b>Color</b>	<b>Various outer colors available</b>														
<b>Lead equivalence</b>	<b>0.5 mm +/- 10%</b>														
<b>Thickness</b>	<b>2.0 mm +/- 10%</b>														
<b>Weight</b>	<b>6 kg/m<sup>2</sup></b>														
<b>Tensile strength (min.)</b>	<b>6 MPa</b>														
<b>Temperature resistance</b>	<b>-40°C to +70°C</b>														
<b>Disclaimer</b>	<p>The information in this data sheet is a result of many years of experience. The details of the product are general statement, and the suitability of the material for a specific application is subject to tests on such applications.</p> <p>The performance of the material when in contact with acids, alkalis and other chemicals may depend on the concentrations and temperatures involved. It may be necessary to perform practical tests.</p> <p>Applications where the material is subject to temperature extremes should be checked by practical tests.</p> <p>Some variations to the physical data given in the data sheet are possible. Refer to our terms and conditions concerning liability.</p>														
<b>Manufacturer</b>	Lead Free Shields														

**Questions regarding the details of this product should be directed to:**

**Lead Free Shields**  
4747 Research Forest Dr  
Ste 180 #139  
The Woodlands, TX 77381

**Tel: (832) 519-8787**  
**Email: [sales@leadfreeshields.com](mailto:sales@leadfreeshields.com)**  
**URL: [www.xraycurtains.com](http://www.xraycurtains.com)**