



ATS1236

32 zones 433Mhz wireless receiver DGP

Increasing zone capacity

The ATS1236 wireless receiver adds wireless capabilities to the Advisor Advanced range of panels.

The wireless DGP supports most of the legacy 433 MHz 63-bit transmitters as well as the new generation of 433 MHz LoNa transmitters of which the wireless communication is fully encrypted, avoiding unauthorized interference. Up to 32 wireless sensors and up to 16 keyfobs can be learned in.

The ATS1236 wireless receiver provides two wired zone inputs and one programmable relay output.

Installation and programming

The wireless DGP needs to be installed outside the panel housing in order to assure a maximum wireless range. The 433MHz wireless solution will monitor the status and presence of each wireless device and will respond in case of an RF jamming condition.

The ATS1236 wireless receiver can be programmed from the keypad as well as from the downloader. The firmware of the module is remotely upgradeable.



Details

- Adds wireless capabilities to Advisor Advanced
- Two wired zone inputs
- One programmable SPDT Form C relay output
- Supports legacy 63-bit 433 MHz and new LoNa 433 MHz transmitters
- Learn-mode technology
- Removable terminals
- EN50131-1/EN50131-3/EN50131-6 Grade 2 Class II (pending) INCERT (pending)
- Firmware upgradeable

Technical specifications

General

Expander type	Wireless expander
Product line	Advisor Advanced
Connection type	Databus connection
Compatibility	Advisor Advanced MR 4.2 or higher

Inputs

Total	32
No. of wireless zones	32 wireless sensors (one way)
Onboard	2 wired

Outputs

Onboard	1
Type of outputs	SPDT Form C relay

Wireless

Operating frequency	433 MHz legacy, 433 MHz LoNa
---------------------	------------------------------

Electrical

Operating voltage	12 VDC via bus
Current consumption	typical 47 mA maximum 51 mA

Physical

Physical dimensions	155 x 95 x 26 mm
Net weight	0.160 kg
Colour	White
Material	ABS plastic

Environmental

Operating temperature	-10°C to +55°C
Relative humidity	90% relative humidity noncondensing
Environment	Indoor

Standards & regulation

Compliance	CE, RoHS
Standards	EN50131 Grade 2 & INCERT pending

