

DESCRIPTION:

Our one hole P-Clips are designed for use on mineral insulated or soft skin fire cables. They are manufactured from copper and are available in LSZH (Low Smoke Zero Halogen) powder coated form. Tested for the requirements in London Underground Ltd Standard Number 2-01001-002 Fire safety performance of materials & Vertical burn test UL 94 V0, V1 & V2.



APPLICATION:

Designed for use on mineral insulated or soft skin fire cables.

SPECIFICATION:

MATERIAL: Copper and Polyester Coating Rated LSF (Low Smoke & Fume).

APPROVALS: Reach compliant

PART NUMBERS:

| PART NUMBER | COLOUR | CABLE SIZE | FOR CABLE DIA. (mm) | PACK SIZE |
|-------------|--------|-------------|---------------------|-----------|
| RCHL26R | Red | 2L1.0 | 6.4 | 50 |
| RCHL26W | White | 2L1.0 | 6.4 | 50 |
| RCHL28R | Red | 2L1.5/3L1.0 | 7.0 | 50 |
| RCHL28W | White | 2L1.5/3L1.0 | 7.0 | 50 |
| RCHL30R | Red | 3L1.5/4L1.0 | 7.9 | 50 |
| RCHL30W | White | 3L1.5/4L1.0 | 7.9 | 50 |
| RCHL32R | Red | 2L2.5 | 7.7 | 50 |
| RCHL32W | White | 2L2.5 | 7.7 | 50 |
| RCHL34R | Red | 3L2.5/4L1.5 | 8.8 | 50 |
| RCHL34W | White | 3L2.5/4L1.5 | 8.8 | 50 |
| RCHL37R | Red | 2L4.0/4L2.5 | 9.2 | 50 |
| RCHL37W | White | 2L4.0/4L2.5 | 9.2 | 50 |

