

## Single Gang Jack Plate for EVC401/PH

Part No. **EVC301/JJ**



### Overview

- A single gang jack plate designed for use in conjunction with an EVC401/JPH portable fire telephone handset on compatible SigTEL emergency voice communication systems.
- Can be mounted on 25mm UK flush or surface single gang back box.
- When the handset (not supplied) is plugged into the Jack Plate it will call the SigTEL master controller from where a two-way speech channel can be opened and instructions communicated.
- Multiple jack plates can be connected to a single SigTEL Master Controller line in stairwells, etc.
- Designed for use in regions where roaming handsets are accepted (typically the Far and Middle East). UK standard BS5839-9 DOES NOT allow the use of these devices.
- Facilitates reliable two-way communication in an emergency between a permanently manned control room and key points of a site.



### More Information

### Technical Specifications

Approvals/certifications	Designed for use in regions where roaming handsets are accepted (typically the Far and Middle East). UK standard BS5839-9 DOES NOT allow the use of these devices.
Supply/operating voltage	11V DC derived from a compatible SigTEL Master Controller (drops to 6 V DC when in use).
Quiescent current	1mA.
Activation current	25mA (current draw when handset is in use).
Indicators	When the operator in the control room calls the outstation, a pulsed ringing tone sounds at the outstation.

# Comsec Protection Systems.

<https://shop.comsec.ie/>



Connections	6.35mm jack socket.
Product dimensions (mm)	85 W x 85 H x 30 D mm (Can be mounted on a standard UK 25mm single gang flush or surface back box).
Construction & finish	Plastic.
IP Rating	IP20.
Weight	58g
Operating conditions/temperature	-5°C to +40°C. Max relative humidity: 95%.



T 01942 322744 E [sales@c-tec.co.uk](mailto:sales@c-tec.co.uk)  
F 01942 829867 W [www.c-tec.com](http://www.c-tec.com)



C-TEC, Challenge Way, Martland Park, Wigan, WN5 0LD United Kingdom