



KL710

KL700 Conventional Temperature Detector Class A2R

General

With outstanding performance, efficiency and durability, the KL700 series conventional fire detectors is the ideal solution for every installation. They are designed specifically for use with Kilsen conventional fire panels, but may also be connected to most 3rd party industry standard conventional fire panels.

A fire detector for every need

With an attractive design and advanced features, the KL700 series has been designed to cope with difficult and even extreme situations. The range includes optical and heat detectors with a universal base that suits every application, including a variant that even compensates for uneven installation surfaces. All detectors support an integral locking mechanism for extra security as well as the connection of a remote indicator.

KL710 Heat Detector

This detector raises an alarm when the temperature exceeds a fixed temperature level or when the programmed rate of the increase of temperature is exceeded. They are used where a fire could cause an abrupt elevation of the temperature, or where smoke of controlled combustion, aerosols, etc. do not allow the use of any other type of detector.

KL731 Photoelectric Smoke Detectors

These detectors use the Tyndall effect of smoke in the chamber to detect a fire. It can detect a smouldering fire (without flames). They are normally used in areas where possible fires generate visible smoke, like plastics, polystyrene, PVC, etc.

The KL731 is available in either white or black colour variants.



Standard Features

- Full line consisting of Optical and Heat detectors
- An ultra-fine grid prevents the ingress of dust and insects in smoke detectors
- Attractive, low-profile design
- EN54 and CPD certified
- Innovative base compensates for uneven surfaces
- Field exchangeable optical chamber for ease of maintenance in optical detectors

KL700 Conventional Temperature Detector Class A2R

Specifications

| | |
|--------------------------------|------------------------------|
| Operating voltage | 18 to 28 VDC |
| Current consumption | |
| Quiescent at 24 VDC | 70 µA |
| Alarm at 24 VDC | < 100 mA |
| Radio-active source | NA |
| Average activity | NA |
| Remote alarm output | < 100 mA |
| Heat specification | Class A2R (60°C and 8°C/min) |
| Operating temperature | -10 °C to +70 °C |
| Storage temperature | -10 °C to +80 °C |
| Max. humidity (non condensing) | 95% |
| IP rating | IP42 |
| Number of detectors per zone | 20 |
| Dimensions (h x Ø) | |
| Head | 45 mm x 99 mm |
| Colour | White RAL9010-P |
| Approvals* | EN54 (BOSEC) |

* Check current status with local office

Ordering Information

| Part No. | Description |
|----------|--|
| KL710 | KL700 Conventional Temperature Detector Class A2R |
| KZ700 | Kilsen KL700 Series Universal Fire Detector Base |
| KZ705 | Kilsen KL700A Series Universal Fire Detector Base |
| KZ705D | Conventional Fire Detector Base with Diode |
| KZD705 | Universal Detector Deep Base with Earth Connection |
| S700 | Surface Mount Accessory for KZ700 and KZ705 Series Bases |
| PA25/3L | Low current remote LED indicator |

