



#### Specifications

Nominal voltage (V)	6
10-hr rate Capacity to 1.8V/Cell at 20°C (Ah)	3.7

#### Dimensions

Length (mm)	70 (±1)
Width (mm)	47 (±1)
Height over terminals (mm)	105.5 (±2)
Mass (kg)	0.87

#### Terminal Type

FASTON - Quickfit / release (JST where stated)	4.75
--	------

#### Operating Temperature Range

Storage (in fully charged condition)	-20°C to +60°C
Charge	-15°C to +50°C
Discharge	-20°C to +60°C

#### Storage

Capacity loss per month at 20°C (% approx.)	3
---	---

#### Case Material

Standard	ABS (UL94:HB)
----------	---------------

#### Charge Voltage

Float charge voltage at 20°C (V)/Block	6.825 (±1%)
Float charge voltage at 20°C (V)/Cell	2.275 (±1%)
Float Chg voltage tmp correction factor from std 20°C (mV)	-3
Cyclic (or Boost) charge Voltage at 20°C (V)/Block	7.26 (±3%)
Cyclic (or Boost) charge Voltage at 20°C (V)/Cell	2.42 (±3%)
Cyclic Chg voltage tmp correction factor from std 20°C (mV)	-4

#### Charge Current

Float charge current limit (A)	No limit
Cyclic (or Boost) charge current limit (A)	1

#### Maximum Discharge Current

1 second (A)	120
1 minute (A)	40

#### Impedance

Measured at 1 kHz (mΩ)	20
------------------------	----

#### Design Life & Approvals

EUROBAT Classification: Standard Commercial	3 to 5 years
Yuasa design life at 20°C (yrs)	up to 5



#### Layout



#### 3rd Party Certifications

ISO9001 - Quality Management Systems



#### Safety

##### Installation

Can be installed and operated in any orientation except permanently inverted.

##### Handles

Batteries must not be suspended by their handles (where fitted).

##### Vent valves

Each cell is fitted with a low pressure release valve to allow gasses to escape and then reseal.

##### Gas release

VRLA batteries release hydrogen gas which can form explosive mixtures in the air. Do not place inside a sealed container.

##### Recycling

YUASA's VRLA batteries must be recycled at the end of life in accordance with local and national laws and regulations.

