

ZP730-2

Addressable Optical Smoke Detector

Reliable sensing for most fire alarm applications

Designed for early response to slow burning, smoldering fires, the ZP730-2 is an addressable smoke detector developed to provide reliable sensing for most fire alarm applications. The detector's proven stability in air movement associated with air conditioning systems has made it a popular selection for modern building interiors.

Operating on light scatter principles, the ZP730-2 fully meets the sensitivity requirements of EN54 Pt 7 and is approved by several international approval bodies.

Automatic self test

False and unwanted alarms are virtually eliminated - smoke levels are continuously sensed by the unit and transmitted via the ZP wiring loop as electronic signals. These are assessed and verified by the control panel prior to any alarm decision being taken.

Installed as part of a ZP addressable system, up to 127 sensing devices may be connected to each of the control panel loops. All loop devices incorporate switch settings enabling them to be assigned a unique address that is polled by the panel every two seconds.

Sensor sensitivity, calibration and self-test are carried out automatically by the ZP system. Removal or replacement of an incorrect sensing device will be identified by the system and shown as a fault. Sophisticated auto contamination adjustment compensates for any drift in performance due to dirt in the sensing chamber.

Locking base option

For ease of removal sensors plug into a range of base units by a simple twist and lock action. A site selectable option is provided to lock the sensor into its base. Once applied the unit can only be removed by means of a special tool.

A red LED indicator situated on the sensor moulding flashes to indicate when the unit is in alarm. Space for address labels is provided on sensor and base mouldings, ensuring units are replaced in their correct location and address numbers can be identified from floor level.



Standard Features

- Responds to slow burning fires
- Complies to EN 54 Pt7
- Analogue sensing - reduces false and unwanted alarms
- Addressable - system knows the status and location of every sensor
- Alarm verification, self test, auto contamination adjustment

Specifications

Model No	ZP730-2
Specification	EN54 Pt7
Description	Addressable optical smoke detector
Sensitivity	2.3% OBS / meter
Compatibility	All ZP addressable systems
Mounting	Plugs into surface or semi recessed base
Area coverage	100m ² subject to local codes
Wiring	2 core loop or spur
Monitoring	Open and short circuit fault, sensor removal and device type
Indication	Alarm LED (red)
Operating voltage	Address line pulsed 20V (19.5V to 20.5V). Max line less 4V
Current	600uA quiescent, 700uA alarm
Addressing method	7 way DIL switches in head
Detection principle	Photo electric light scatter
Application	Indoor installation
EN60529 rating	IP32
Temperature range	-10°C to +75°C
Humidity range	20% to 95% RH (non condensing)
EMC	CE marked (EEC89/336)
Material	Moulded ABS
Dimensions	106mm (dia) x 52mm (h) (excluding base)
Height	60mm ZP7-SB1 surface base, 38mm ZP7-RB1 recessed base
Colour	White
Weight	105g (excluding base)
Publication No	PS1244

Ordering Information

Part No.	Description
ZP730-2	Addressable Optical Smoke Detector
ZP7-SB1	Addressable Detector Base - Surface Mounting
ZP7-RB1	Analogue sensor base - recessed
ZP7-IB	Sensor base isolator

Comsec Protection Systems.
 26 Stadium Business Park, Dublin D11 FY81
 Tel +353 1 8853008 Email info@comsec.ie www.comsec.ie

