

DMN700R470

Conventional MCP, Flush Mount, Red, 470Ω & Free Contact With Glass

General

The DMN700R470 is a red manual call point for flush mount applications. It has an internal 470 ohm series resistor and a potential free contact. It is supplied with a break glass and test key. Surface mount applications require the addition of the DMN787 surface mount box.

Installation

Installation efficiency, flexibility and full compliance with the latest standards are at the heart of the DMN700 MCP indoor call point range. Installation time and ultimately cost, are of paramount importance.

The DMN700 range directly reflects this need by providing a unique 'plug and play' concept designed specifically to reduce installation time. All DMN700 products utilise a special terminal block where all initial installation cabling is terminated. This terminal block is then simply connected to the back of the MCP. Simple, but effective, with no re-termination required and no time wasted.

Options and approvals

Through new standards and legislation, both break glass and re-settable operating elements may be used. To provide the greatest 'flexibility', the DMN700 range can be configured as either a break glass or re-settable unit by simply changing from one element to another. No other additional parts or alternative products are required.

Full compliance with the latest standards is essential and the new MCP indoor call point range is fully approved to the latest EN54-11 standard.



Details

- Enhanced aesthetics
- Easy to install (plug and play)
- Surface mount options
- Protection hinged cover with Anti-Tamper facility
- Backward compatible
- Key test facility
- May be used with glass or resettable element
- Easy to replace glass
- High quality micro switch
- Fully approved to the latest standards

Comsec Protection Systems.

DMN700R470

Conventional MCP, Flush Mount, Red, 470 Ohm, Free Contact With Glass

<https://shop.comsec.ie/>

Technical specifications

Isolation

Series resistance 470 ohm

Physical

Net weight 110 g

Colour Red

Material (body) PC/ABS

Environmental

Operating temperature -10 to +55°C

Storage temperature -10 to +55°C

Relative humidity 0 to 95% noncondensing

Environment Indoor

IP rating IP24D

Standards & regulation

Certification EN54-11

Cable Termination

0.5 - 2.5 mm²

Max. contact rating (resistive load)

2A @ 30 VDC

As a company of innovation, UTC Fire & Security reserves the right to change product specifications without notice. For the latest product specifications, visit UTC Fire & Security online or contact your sales representative.

Last updated on 12 August 2019 - 15:30

