

The 1350/1360 series is a range wall mounted electromagnetic door retainers that offers the user a choice of holding strengths.

Robust and simple to install, they are ideal for a wide range of applications such as nursing homes, hospitals, schools and industrial premises. Doors can be held open under normal conditions and then automatically released in the event of a fire alarm activation.

24Vdc

25-45mA / 40-100mA

Steel / ABS cover

10°C to +55°C IP40

800g / 1000g

White / Black

len

25-50Kg 245-490N /50-100Kg 490-960N

Wall mounting / Floor bracket available

Features

- Versatile holding settings
- High holding force •
- Low current consumption
- Release button and protection circuit •
- Adjustable damping keeper plate •
- Protection diodes as standard ٠

Benefits

- Flexibility in installation
- Suitable for large and small fire doors
- Requires less power from your system ٠
- Requires less power from your system Door can be manually closed when not activated by • the fire system
- Allows for door misalignment

Dimensions



Catalogue Numbers

Reference	Cat No	Description
FSMD/024/40/W/DIODE	1350-CSA	Wall Mounted Magnetic Door Release 24Vdc, 40Kgf/390N (includes diode protection circuit)

Technical Specifica

Holding Force

Voltage

Current

Mounting

Protection

Body Colour

Weight

lousing Material

emperature Range