



877-459-4585



877-817-5716
equipment@turnkeyparlor.com
1289 Fordham Blvd Suite 117 Chapel Hill NC 27514

VisiDipper

The VisiDipper is the most innovative design for ice cream dipping cabinets in over 25 years.

VisiDipper provides 75% more product viewing area than standard canopy dipping cabinets and features a unique air piston-assisted, tempered, scratch-proof service-side lid for no-hands easy opening.

The VisiDipper product line features both straight and curved glass models in 4-can, 8-can, 12-can, and 16-can models.



FEATURES:

- New refrigerant/compressor design
- Microprocessor digital controller with LED digital display
- 4½" lower front glass offers 75% more product viewing area
- Improved energy efficiency, reliability and quieter operation
- Stainless-steel top service area
- Slide-out condensing unit for easy maintenance and serviceability
- Additional storage capacity underneath product display level

- Energy Star compliant
- Temperature range 10°F to -15°F
- Durable powder-coat paint finish interior and exterior
- 8-foot 15A power cord with NEMA 5-15 plug
- Manual defrost

OPTIONAL ACCESSORIES:

- Can skirt kits
- Caster kits
- Dipperwell
- Gelato pan racks (pans not included)
- Frost shield kits
- Leg kits

formerly
Kelvinator

Project:

Quantity:

Item#:

Model Specified:


Approval: _____

KDC-V/CKDC-V VisiDipper Ice Cream Dipping Cabinets





TECHNICAL DATA

MODEL	KDC/CKDC27V	KDC/CKDC47V	KDC/CKDC67V	KDC/CKDC87V
Temp Range	+10°F to -15°F	+10°F to -15°F	+10°F to -15°F	+10°F to -15°F
Exterior Dimensions				
Length	25.75	46.5"	67"	88"
Depth	26.75	26.75"	26.75"	26.75"
Height	51.81	51.81"	51.81"	51.81"
Capacity	4.6 cu. ft.	12.0 cu. ft.	19.1 cu. ft.	26.4 cu. ft.
Capacity (3-gal. tubs)	4	12	20	28
Facings (3-gal. tubs)	4	8	12	16
Storage (3-gal. tubs)	0	4	8	12
Compressor	Hermetic	Hermetic	Hermetic	Hermetic
Shipping Weight	235 lbs.	365 lbs.	525 lbs.	635 lbs.
Condensor Type	Bare Tube	Bare Tube	Bare Tube	Bare Tube
Lighting	LED	LED	LED	LED
Electrical	115/60/1	115/60/1	115/60/1	115/60/1
Rated Amps	11.0	11.5	12.5	12.5

**STRAIGHT GLASS
SIDE VIEW**



**CURVED GLASS
SIDE VIEW**




SPECIFICATIONS

Item: _____ KDC _____ V

Furnish () quantity. VisiDipper Ice Cream Dipping Cabinets, Kelvinator model _____ KDC _____ V. The unit construction shall consist of a 20-ga. white powder-coat finished galvanized steel interior and exterior, foamed in place. The unit will be supplied with an air piston-assisted, tempered, scratch-proof service-side lid and a stainless-steel top service area.

Cabinet as specified to use R-404a refrigerant. Refrigeration control shall be thermostatic control with a temperature range of 10°F to -15°F. Cabinet to have independent on/off switch for compressor and light switch to be mounted in the shell of the cabinet and to be furnished with a drain connection. Cabinet to be provided as a rear-air intake and front-air discharge (consult factory for rear-air intake and discharge).

ELECTRICAL CONNECTION



877-459-4585

Global Refrigeration, Inc., reserves the right to change specifications, terms, and prices without notice.



877-817-5716
equipment@turnkeyparlor.com
1289 Fordham Blvd Suite 117 Chapel Hill NC 27514