# Models 751/8751 Specifications

# Freezing Cylinder

One, 3.4 quart (3.2 liter) volume.

# Mix Hopper

One. 20 quart (18.9 liter) capacity.

#### **Beater Motor**

One.1.5 hp.

# Refrigeration Unit

One, approximately 9,500 btu/hr compressor. Refrigerant R404A. One independent (SHR) compressor, approximately 400 btu/hr. Refrigerant R134a. (BTU's may vary based on compressor used.)

### **Electrical**

Electrical	One dedicated connection.	
	Maximum	Minimum
Model 751	Fuse Size	Circuit Ampacity
208-230/60/1 Air	35	26
208-230/60/1 Water	30	24
208-230/60/3 Air	25	19
208-230/60/3 Water	20	17
Model 8751		
208-230/60/1 Air	35	28
208-230/60/1 Water	35	25
208-230/60/3 Air	25	21
208-230/60/3 Water	25	18

These units are manufactured in other electrical characteristics. Refer to the Distributor Data Book for availability. (For exact electrical information, always refer to the data label of the unit.)

## Air Cooled

Clearance: 3" (7.6 cm.) around all sides. A deflector has been added to underside preventing recirculation of warm air. This will assure proper air flow across condensers to obtain optimum performance.

### **Water Cooled**

Water inlet and drain connections 3/8" FPT.

## **Dimensions**

Width: 18-7/16" (46.8cm.) Depth: 31-3/16" (79.2 cm.) Height: 59-7/8" (152.1 cm.)

Floor Clearance: 7-1/2" (19.1 cm.) mounted on

standard casters.

# **Approximate Weights**

#### Model 751:

Net: 455 lbs. (201.9 kgs.) Crated: 476 lbs. (215.9 kgs.),

35.4 cu. ft. (.99 cu. m.)

#### Model 8751:

Net: 480 lbs. (217.7 kgs.) Crated: 501 lbs. (227.2 kgs.),

35.4 cu. ft. (.99 cu. m.)

Availability and specifications are subject to change without notice.

These units are designed and constructed to meet stringent safety and sanitation requirements for NSF and UL.

