



T30 LGP

T50 LGP



T80 LGP

TOP MOUNT GLASS-DOOR VERTICAL MERCHANDISERS

Low-Temperature Glass-Door Freezers

Globals low temperature glass door merchandisers are designed to enhance your product sales through improved merchandising. The cabinets offer an extra large viewing area and the brilliant LED lighting illumination magnifies the appeal of your products.

Top mount merchandisers are available in one, two and three door models. The option of several sizes makes it easy to create merchandising walls of variable length using standard units. Adjustable cantilever shelves provide an extra realm of flexibility.



All products are certified for energy , safety and sanitation. NSF/ ANSI 7 Standards

FEATURES

- Digital temperature controller with programmable defrost options and LED display
- LED Lighting for brilliant illumination
- Patented Kelvinator refrigeration design
- Interior cavity temperature 0°F to -20°F
- Optional stainless steel exterior
- 20 gauge steel cabinet with white powder coat paint interior & exterior
- Triple pane heated glass doors and heated perimeter and mullions prevent and clear condensation from glass and frame of freezer
- Full height glass doors provide 35% more product visibility.
- Includes 4 adjustable cantilever shelves & 1 bottom shelf per door opening
- Dual fan and extended evaporator coil produce low frost accumulation on walls of cabinet
- Fin coil and forced air evaporator improve air flow and performance
- Expansion valve refrigerant control provides quick pull down and reduces compressor run time.
- Highest capacity evaporator coil improves performance of unit
- Heated drain pan dissipates condensation , no plumbing required
- Auto Door Fan Switch technology eliminates frost & icing issues on products
- Top mounted condensing unit provides unobstructed air flow
- Independent on/off switch for compressor and lights
- Energy star qualified

OPTIONAL ACCESSORIES

- Cantilever Shelf
- Bottom Shelf
- Shelf Kits
- Caster Kit
- Skirt Kits

TOP MOUNT VERTICAL MERCHANDISERS

TECHNICAL DATA



MODEL	T30 LGP	T50LGP	T80 LGP
Temp Range	0°F to -20°F	0°F to -20°F	0°F to -20°F
Exterior Dimensions			
Length	31"	52"	78"
Depth	36 ¹ / ₄ "	36 ¹ / ₄ "	36 ¹ / ₄ "
Height	83 ³ / ₄ "	83 ³ / ₄ "	83 ³ / ₄ "
Interior Dimensions			
Length	26 ¹ / ₄ "	47 ¹ / ₄ "	73 ¹ / ₄ "
Depth	29 ⁵ / ₈ "	29 ⁵ / ₈ "	29 ⁵ / ₈ "
Height	60 ⁵ / ₈ "	60 ⁵ / ₈ "	60 ⁵ / ₈ "
Capacity	27.3 cu. ft.	49.1 cu. ft.	76.2 cu. ft.
Shipping Weight	650 lbs.	900 lbs.	1,200 lbs.
Electrical	115V	208-230/115V	208-230/115V
Fuse Size	20	20-30	20-30
Rated Amps	13.5	9.5	16.0

SPECIFICATIONS

T30, T50, T80LGP

Top mount low temperature merchandiser, Global model T___LGP. The unit shall consist of white powder coat finished galvanized steel interior & exterior, foamed in place. The unit will be supplied with 4 cantilever shelves and a bottom shelf per door opening.

Cabinet as specified to use R-404A refrigerant. Refrigeration control shall be thermostatic control with a temperature range of 0°F to -20°F. Cabinet to have independent on/off switch for compressor and lights.



Cabinet designed for optimum performance in air-conditioned area at 70°F to 75°F ambient temperature and 50% to 55% relative humidity.

Global Refrigeration, Inc., reserves the right to change specifications, terms, and prices without notice.

Global Refrigeration, Inc.

5855 Grant Avenue, Cleveland, OH 44105

888.650.9799

www.globalref.com