



**ROBERTS Reel to Reel
Tape Recorder 770X**

MODEL 770X SCHEMATIC
ROBERTS ELECTRONICS
DIVISION OF PHEEM MANUFACTURING CO.
SCHEMATIC NO. 8-1012

UNLESS OTHERWISE NOTED:
ALL RESISTANCE VALUES IN OHMS, Ω M
ALL CAPACITANCE VALUES IN MICROFARADS AT 400V DC

REGARD SLIDING LINKAGE TO RT CH. IS DISCONNECTED MECHANICALLY WHEN SOUND WITH SOUND BUTTON IS DEPRESSSED, LEAVING RT CH. IN PLAY MODE.

REC. STOP P.I.B. STOP

REC. STOP P.I.B. STOP

REC. STOP P.I.B. STOP

REC. STOP P.I.B. STOP

REC. STOP P.I.B. STOP

REC. STOP P.I.B. STOP

REC. STOP P.I.B. STOP

REC. STOP P.I.B. STOP

REC. STOP P.I.B. STOP

REC. STOP P.I.B. STOP

REC. STOP P.I.B. STOP

REC. STOP P.I.B. STOP

REC. STOP P.I.B. STOP

REC. STOP P.I.B. STOP

REC. STOP P.I.B. STOP

REC. STOP P.I.B. STOP

REC. STOP P.I.B. STOP

REC. STOP P.I.B. STOP

REC. STOP P.I.B. STOP

REC. STOP P.I.B. STOP

REC. STOP P.I.B. STOP

REC. STOP P.I.B. STOP

REC. STOP P.I.B. STOP

REC. STOP P.I.B. STOP

REC. STOP P.I.B. STOP

REC. STOP P.I.B. STOP